

An Employee Owned Company

CWC Premium Series

Industrial Cold Water Pressure Washers

<section-header>

The CWC Series is an ideal choice for heavy-duty jobs. Equipped with a robust, rugged roll cage, it is a great option for cleaning ag, construction and industrial equipment.

PUMP

- External bypass system protects from heat build-up
- Forged brass manifold
- Thermal and safety relief valves
- Water filter with clear sleeve for screen inspection (High capacity water filter on CWC-3008-4MGH)

ENGINE

• Electric start - sealed battery included

FRAME

- Powder coated steel frame with roll cage and lifting hook
- Two-piece belt guard
- 13-inch flat-free tires with locking tire brake

COMPONENTS

- Fuel tank has powder coated outside and aluminized steel inside to prevent rusting
- 13-gallon fuel tank capacity for 9½ hour run time

UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x $^{\scriptscriptstyle 3\!\!/}_{\scriptscriptstyle 8}\text{-inch non-marking hose}$ (CWC-5000 and CWC-6004 models)
- 50-foot x ³/₆-inch black hose (CWC-7004-4MGH)
- 50-foot x ½-inch black hose (CWC-3008-4MGH)
- Insulated trigger gun

LIMITED WARRANTIES

- 3 year Honda, Mi-T-M and Vanguard engines
- 7 year AR and General pumps

CERTIFICATION

• ETL Certified - US (Select models, see chart)



CWC Premium Series Cold Water – Gasoline – Portable with Roll Cage – Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CWC-3008-4MGH	3000	8.0	688cc Honda GX630 OHV	General	Factory preset	48in.	43x27.75x38.5in.	504 lb.	438 lb.
CWC-5004-4MAH*	5000	4.0	688cc Honda GX630 OHV	AR	Factory preset	48in.	43x27.75x38.5in.	499 lb.	433 lb.
CWC-5004-4MAM	5000	4.0	670cc Mi-T-M OHV	AR	Factory preset	48in.	43x27.75x38.5in.	499 lb.	433 lb.
CWC-5004-4MAV	5000	4.0	480cc Vanguard OHV	AR	Factory preset	48in.	43x27.75x38.5in.	499 lb.	433 lb.
CWC-5004-4MGH*	5000	4.0	688cc Honda GX630 OHV	General	Factory preset	48in.	43x27.75x38.5in.	515 lb.	449 lb.
CWC-5005-4MGH*	5000	5.0	688cc Honda GX630 OHV	General	Factory preset	48in.	43x27.75x38.5in.	515 lb.	449 lb.
CWC-5005-4MGM	5000	5.0	670cc Mi-T-M OHV	General	Factory preset	48in.	43x27.75x38.5in.	515 lb.	449 lb.
CWC-6004-4MGH	6000	3.7	688cc Honda GX630 OHV	General	Factory preset	48in.	43x27.75x38.5in.	515 lb.	449 lb.
CWC-7004-4MGH	7000	3.8	688cc Honda GX690 OHV	General	Factory preset	48in.	43x27.75x38.5in.	515 lb.	449 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory. *ETL Certified – US.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0089	50-foot x 1/2-inch hose - For when you need extra hose for added mobility	CWC-3008-4MGH
851-0317	50-foot x %-inch non-marking hose - For when you need extra hose for added mobility	CWC-5004, CWC-5005 & CWC-6004 models
851-0420	50-foot x %-inch hose - For when you need extra hose for added mobility	CWC-7004-4MGH
AW-7012-7004	Power broom with rotating nozzle – Rotating nozzle with two wheels for easy mobility, 3.0 orifice size	CWC-7004-4MGH
AW-7500-0035	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.5 orifice size	CWC-5004 models
AW-7500-0045	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 4.5 orifice size	CWC-5005 models
AW-0018-0374	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage, 3.0 orifice size	CWC-6004 & CWC-7004 models
CX-0118	Skid feet – Stationary applications	All models



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.