Built for optimum performance and productivity, the versatile portable or stationary 20-gallon air compressor is built with an abundance of air storage capacity.

20-Gallon



Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Frame:

- Powder coated ASME coded 20-gallon receiver tank
- ¾6-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard
- Flat-free tires (AM2-PH09-20M)

Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 161/2-inch fly wheel
- Quality pilot valve unloader

Limited Warranties:

- 2 year pump exchange (see page 66 for more information)
- 3 year Honda engine

Certifications:

 ASME Boiler and Pressure Vessel Code - UM

Two Stage - Gasoline

PORTABLE								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	20-gallon	Pneumatic	46x26x39.5in.	356 lb.	306 lb.
STATIONARY								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	20-gallon	Pneumatic	37x18x38in.	356 lb.	306 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	
AW-0007-0196	Rear lifting handle (N/A for models with AX-0017 option)	AM2-PH09-20M	
AW-6000-1002	Equipment cover	All models	
AX-0003	Manual drain/regulator/metal bowl	All models	
AX-0015	Electric start - battery and cables not included	All models	

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0017		
IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0015	All models