

Heat your space quietly and efficiently while providing instant heat without the need of electricity. The gas-fired convection heater is perfect for workshops, construction sites, farm sites and loading docks with proper ventilation.

# Gas-Fired Convection



MH-0080-CM10

**Frame:**

- Quick assembly 2-piece burn chamber
- Durable steel housing
- Inner windshield protects burner flame from being extinguished

**Heat Output:**

- Variable heat settings
- 360-degree heat radius for even heating of room

**Components:**

- Matchless piezo spark ignition
- Automatic shut-off if flame is extinguished

**Limited Warranty:**

- 1 year

**Certifications:**

- CSA Certified - US and Canada
- CSA Blue Star Certified - US Only
- CSA Blue Flame Certified - Canada Only

**Important Notes:**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Extremely hot during operation. Keep children, animals and all combustible objects away from heater.

## 50,000 up to 200,000 BTU

| MODEL NO.                     | MH-0080-CM10         | MH-0100-CM1N                        | MH-0200-CM10        |
|-------------------------------|----------------------|-------------------------------------|---------------------|
| HEAT OUTPUT                   | 60-80,000 BTU        | 50-100,000 BTU                      | 50-200,000 BTU      |
| HOT-AIR FLOW                  | N/A                  | 400 CFM                             | N/A                 |
| IGNITION TYPE                 | Automatic (integral) | Control knob ignition               | Push-button         |
| FUEL                          | Propane              | Natural Gas                         | Propane             |
| FUEL CONSUMPTION              | 2.3 / 3.7 lb./hr.    | 2.13 minimum / 4.63 maximum lb./hr. | 3.24 / 9.25 lb./hr. |
| OPERATING TIME (100 LB. CYL.) | 43 / 27 hours        | N/A                                 | 31 / 11 hours       |
| OPERATING TIME (40 LB. CYL.)  | 17 / 11 hours        | N/A                                 | N/A                 |
| OPERATING TIME (20 LB. CYL.)  | 8 / 5 hours          | N/A                                 | N/A                 |
| SUGGESTED CYLINDER SIZE       | 100 lb.              | N/A                                 | 100 lb.             |
| INLET GAS PRESSURE            | N/A                  | 7in. WC minimum / 14in. WC maximum  | N/A                 |
| HEATING AREA                  | 1,800 sq. ft.        | 3,000 sq. ft.                       | 4,600 sq. ft.       |
| STAINLESS-STEEL BURNER        | No                   | Yes                                 | No                  |
| HOSE & REGULATOR              | Yes, 10 ft.          | No                                  | Yes, 10 ft.         |
| DIMENSIONS (LxWxH)            | 15.7x15.7x21.8in.    | 15.7x15.7x26.4in.                   | 16x16x26.4in.       |
| SHIP WT.                      | 17 lb.               | 21 lb.                              | 20 lb.              |
| NET WT.                       | 11.5 lb.             | 14.3 lb.                            | 14 lb.              |

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

**Accessory:**

| PART NUMBER | DESCRIPTION           | FITS MODELS |
|-------------|-----------------------|-------------|
| 68-5010     | Two cylinder manifold | All models  |