Water Trailer

Control dust on every jobsite with the Mi-T-M dual-axle, 510-gallon water trailer. Offering rear spray, fire and garden hose hook-ups and hydrant fill capabilities, this tough and durable water trailer is perfect for cleaning parking lots, heavy equipment, streets and a host of other applications. Paired with a 2-inch semi-trash pump this combination can tackle any job requiring portable water.

Tank:

- 510-gallon elliptical low profile %-inch thick polyethylene
- 16-inch manhole with 4-inch vent and sump drain

Central Manifold:

- Easy-to-operate butterfly brass valves

Plumbing:

- 1½-inch fire hose hook-up with 50-foot x 1½-inch hose and fog nozzle
- Break-away hydrant fill with 25-foot x 2½-inch hose
- Dual rear spray heads
- Garden hose connector
- Manifold discharge system
- Water hammer prevention valve

Trailer:

- DOT approved
- 12-inch underclearance at axle
- 7,000-lb. side-mount crank jack
- Dual leaf spring suspension
- Rubber mounted sealed lights
- Wire storage basket
- Two safety chains with snap hooks

Semi-Trash Pump:

- 2-inch suction and discharge that handles solids up to ¾-inch
- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Silicon carbide mechanical seals
- Precision molded cast iron impeller and volute for reduced vibration and wear

Limited Warranties:

1 year trailer2 year pump

- 3 year Honda engine

- 3 year water tank



MODEL NUMBER	DISPLACEMENT/ ENGINE	PUMP	COUPLER	TIRES	AXLES	BED FRAME	DIMENSIONS (LxWxH)	TRAILER WT. (EMPTY)	TRAILER WT. (LOADED)
MWT-0510-2MHD	118cc Honda GX120 OHV	2in. semi-trash	2in.	` '	(2) 3,500 lb. tandem with hydraulic surge brakes	5ft.x8ft.	13ft. 7in.x82in.x70in.	1,580 lb.	5,900 lb.

Option:

PART NUMBER	DESCRIPTION
TX-0008	Hard suction option - Allows you to draw water from an auxiliary source (pond, water pit, etc.). The fire hose is designed to be used with pressurized water and
	lays flat for easy storage.