

The Mi-T-M trash pumps feature a 3 or 4-inch suction and discharge that handles solids up to 1-inch in diameter and is powered by an industrial Honda OHV engine. They are ideal for construction and agricultural applications.

WTP-T03-OMGH shown with 3-in. suction and discharge kit, 70-0525



Trash Pumps

Frame:

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Rubber isolators minimize vibration

Components:

- Durable silicon carbide mechanical seals
- Cast iron impeller and volute for reduced vibration and wear
- Die cast aluminum pump is lightweight and portable
- The clean-out cover and volute can be removed for easy cleaning of debris

Limited Warranty:

- 2 year pump
- 3 year Honda engine



Suction and discharge kit, 70-0661

3 & 4-Inch

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAX. TOTAL HEAD	MAX. CAPACITY	SUCTION LIFT	SOLIDS HANDLING CAPABILITY	PSI	DISPLACEMENT/ENGINE	START	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-T03-OMGH	3in.x3in.	95ft.	370 GPM	26ft.	Up to 1in. diameter	38	270cc Honda GX270 OHV	Recoil	1.39 gallons	29x21.8x22.5in.	177 lb.	152 lb.
WTP-T04-OMGH	4in.x4in.	95ft.	580 GPM	26ft.	Up to 1in. diameter	38	389cc Honda GX390 OHV	Recoil	1.6 gallons	29x21.8x22.5in.	192 lb.	167 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
15-0294	20-ft. x 3-in. green PVC hard suction hose with fittings	WTP-T03-OMGH	15-0356	20-ft. x 4-in. green PVC hard suction hose with fittings	WTP-T04-OMGH
15-0296	50-ft. x 3-in. blue PVC soft discharge hose	WTP-T03-OMGH	15-0357	50-ft. x 4-in. blue PVC soft discharge hose	WTP-T04-OMGH
19-0629	3-in. steel suction strainer with round openings	WTP-T03-OMGH	19-0277	4-in. steel suction strainer with round openings	WTP-T04-OMGH
70-0525	3-in. suction and discharge kit	WTP-T03-OMGH	70-0661	4-in. suction and discharge kit	WTP-T04-OMGH
AW-5740-0017	Wheel kit	All models			