



An
Employee
Owned
Company

14000-Watt Portable Gasoline Generators



GEN-14000-1MHE

This 14000-watt generator is built to withstand even the most demanding applications. It is designed with portability in mind, making it easy to move from one job to the next.

ALTERNATOR

- Total harmonic distortion (THD) less than 5%
- Copper windings

FRAME

- Reinforced power coated steel frame
- 13-inch flat-free tires

COMPONENTS

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone muffler
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner
- USDA/USFS-approved spark arrestors

LIMITED WARRANTIES

- 2 year alternator
- 3 year engine

CERTIFICATION

- CSA Certified (GEN-14000-1MHE)



14000-Watt Portable Gasoline Generators

MODEL NUMBER	GEN-14000-1MHE	GEN-14000-1MME
MAX. AC OUTPUT	14000 watts	14000 watts
RATED AC OUTPUT	12000 watts	12000 watts
DISPLACEMENT/ENGINE	688cc Honda GX630 OHV with electric start – sealed battery included	670cc Mi-T-M OHV with electric start – sealed battery include
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	116.7/58.3	116.7/58.3
CONT. AMPS (120V/240V)	100.0/50.0	100.0/50.0
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A
CIRCUIT BREAKERS	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole (1) 50A toggle circuit breaker, double pole	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole (1) 50A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	77.5	80.0
FUEL CAPACITY	13.2 gallons	13.2 gallons
RUN TIME (AT FULL LOAD)	8.0 hours	8.0 hours
DIMENSIONS (LxWxH)	31.5x30.5x37.5in.	31.5x30.5x37.5in.
SHIP WT.	568 lb.	553 lb.
NET WT.	508 lb.	493 lb.


Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODEL
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators.	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODEL
GX-0003	Skid feet – For stationary applications	All models
GX-0005	50A twist lock receptacle – Marine receptacle for routine marine applications	All models



GFCI 5-20R



NEMA L14-30R
120V/240V



NEMA 14-50R
50A



NEMA L5-30R
120VAC



GX-0005 option
CS6369A
50A twist lock
receptacle



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.