

An Employee Owned Company

# 14000-Watt

### Industrial Gasoline

The most grueling jobs are no match for the 14000-watt generator, and it's designed to move easily from one job to the next.



#### **ALTERNATOR**

- Total harmonic distortion (THD) less than 5%
- Copper windings

#### **ENGINE**

• Electric start – sealed battery included

#### FRAME

- Reinforced powder coated steel frame
- 13-inch flat-free tires

#### COMPONENTS

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone muffler
- · Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- · Heavy-duty industrial air cleaner
- USDA/USFS-approved spark arrestors

#### LIMITED WARRANTY

• 3 year engine

#### **CERTIFICATION**

CSA Certified (GEN-14000-1MHE)

MODEL NUMBER	GEN-14000-1MHE	GEN-14000-1MME		
MAX. AC OUTPUT	14000 watts	14000 watts		
RATED AC OUTPUT	12000 watts	12000 watts		
DISPLACEMENT/ENGINE	688cc Honda GX630 OHV+	670cc Mi-T-M OHV		
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz		
MAX. AMPS (120V/240V)	116.7/58.3	116.7/58.3		
CONT. AMPS (120V/240V)	100.0/50.0	100.0/50.0		
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) 120V/240V, 50A		
CIRCUIT BREAKERS	<ul><li>(2) 20A toggle circuit breakers, single pole</li><li>(1) 30A toggle circuit breaker, single pole</li><li>(1) 30A toggle circuit breaker, double pole</li><li>(1) 50A toggle circuit breaker, double pole</li></ul>	<ul><li>(2) 20A toggle circuit breakers, single pole</li><li>(1) 30A toggle circuit breaker, single pole</li><li>(1) 30A toggle circuit breaker, double pole</li><li>(1) 50A toggle circuit breaker, double pole</li></ul>		
RATED SPEED	3600 RPM	3600 RPM		
DECIBEL RATING	77.5	80.0		
FUEL CAPACITY	13.2 gallons	13.2 gallons		
RUN TIME (AT FULL LOAD)	8.0 hours	8.0 hours		
DIMENSIONS (LxWxH)	31.5x30.5x37.5in.	31.5x30.5x37.5in.		
SHIP WT.	568 lb.	553 lb.		
NET WT.	508 lb.	493 lb.		
Naisa layal taatad at asyan mataya (750), laad). Dating yanyaganta minimyy naisa layal yating				

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating. +49 state engine. Not for sale in California.

# 14000-Watt

# Portable Generators - Industrial Gasoline

ACCESSORIES:			
PART NUMBER	DESCRIPTION	FITS MODEL	
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators.	All models	
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models	
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models	

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODEL
GX-0003	Skid feet – For stationary applications	All models
GX-0005	50A twist lock receptacle – Marine receptacle for routine marine applications	All models











-30R NEMA 14-50R NEMA L5-30F OV 50A 120VAC

CS6369A 50A twist lock receptacle





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.