



An
Employee
Owned
Company

20-Gallon

Industrial Two Stage — Gasoline

Remote jobsites require dependable power, and the two-stage, 20 gallon air compressors deliver reliable performance.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard
- 13-inch flat-free tires (Portable models)

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valve for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader
- Start/stop control set at 145 to 175-PSI

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM



AM2-SH09-20ME

PORTABLE MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	46x26x39.5in.	356 lb.	306 lb.
AM2-PH09-20ME^	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	46x26x39.5in.	363 lb.	313 lb.
AM2-PM09-20M	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	46x26x39.5in.	356 lb.	306 lb.
AM2-PM09-20ME^	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	46x26x39.5in.	363 lb.	313 lb.

STATIONARY MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	37x18x38in.	356 lb.	306 lb.
AM2-SH09-20ME^	17.2 @ 175	270cc Honda GX270 OHV	Pneumatic	37x18x38in.	363 lb.	313 lb.
AM2-SM09-20M	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	37x18x38in.	356 lb.	306 lb.
AM2-SM09-20ME^	17.2 @ 175	300cc Mi-T-M OHV	Pneumatic	37x18x38in.	363 lb.	313 lb.

*Equipped with 150-PSI maximum rated regulator.

^Equipped with electric start – battery, box and cables not included.

20-Gallon

Air Compressors – Industrial Two Stage – Gasoline

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
854-0093	Service truck mount kit – Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications	Stationary models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0017	Battery, battery tray, box and 2-foot of cables – Attaches to engine side on unit	Electric start models
AX-0077	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	Electric start models
AX-0101	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PH09-20ME & AM2-SH09-20ME
AX-0105	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PM09-20ME & AM2-SM09-20ME



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.