

30-Gallon Two Stage – Gasoline

Compressor Pump:

Splash lubricated | Stainless-steel braided discharge hose | Large canister intake filter | Oil level sight indicator

Generator:

Brushless alternator | Total harmonic distortion (THD) less than 6% | 100% copper windings | Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

Frame:

Powder coated ASME coded 30-gallon receiver tank | 3/16-inch base plate to reduce vibration | 16-gauge powder coated two-piece belt guard

Components:

Regulator and two gauges for tank and outlet pressure | Manual drain valves for proper maintenance | 16 1/2-inch fly wheel | Quality pilot valve unloader

Limited Warranties:

1 year Mi-T-M engine | 2 year alternator | 2 year pump exchange (see page 73 for more information) | 3 year Honda and Kohler engines

Certification:

ASME Boiler and Pressure Vessel Code - UM



AG2-SH13-30M



NEMA 5-20R,
125V



NEMA L6-20R,
240V



Featuring an industrial air compressor and generator combination, this machine is durable even in the toughest environments. Whether it's oil fields or farm fields, this versatile machine will deliver enough power to get the job done. Engineered to reduce the space necessary to fit in work and service trucks, this combination unit will meet the needs of mobile mechanics.

30-Gallon

Two Stage – Gasoline



AG2-SK14-30M

AIR COMPRESSOR/GENERATOR COMBINATIONS

MODEL NUMBER	CFM @		MAX. OUTPUT	ALTERNATOR WATTAGE		RECEPTACLES	DISPLACEMENT/ENGINE	COMPRESSOR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	90 PSI	175 PSI*		CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD						
AG2-SH13-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	389cc Honda GX390 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SK14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	429cc Kohler CH440 OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.
AG2-SM14-30M	16.4	15.7	4000 watts	2300 watts	3500 watts	(2) NEMA 5-20R, (1) NEMA L6-20R	420cc Mi-T-M OHV	Two stage, cast iron	40x24.5x45in.	550 lb.	450 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
70-0358	Engine oil drain extension	All models	AX-0074	Electric start - battery box and cables included, battery not included	AG2-SM14-30M
AW-6000-1002	Equipment cover	All models	AX-0075	Idle down - includes electric start - battery not included	AG2-SM14-30M
AX-0019	Electric start - battery, box and cables not included	AG2-SH13-30M	IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use. Recommended for models that are mounted in service truck applications	All models
AX-0063	Lifting hook	All models	IX-0055	Remote start/choke: 6-ft. wire extension for key switch. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	AG2-SH13-30M
AX-0064	Electric start - battery box and cables included, battery not included	AG2-SH13-30M	IX-0059	Remote start/choke: 6-ft. wire extension for key switch, sealed cable. You will also need to order electric start option, AX-0019 or idle down option, AX-0068.	AG2-SH13-30M
AX-0068	Idle down - includes electric start - battery not included	AG2-SH13-30M			
AX-0070	Battery tray, box and 2-ft. of cables	All models			
AX-0071	Electric start - battery, box and cables not included	AG2-SK14-30M			
AX-0072	Electric start - battery box and cables included, battery not included	AG2-SK14-30M			
AX-0073	Electric start - battery, box and cables not included	AG2-SM14-30M			