

# CW Premium Series

## Cold Water – Gasoline – Belt Drive

Known as the workhorse of the Mi-T-M industrial pressure washer line, the durable CW Premium Series takes cleaning to the next level. It is built for extended cleaning applications and has what it takes to get the big jobs done.



CW-3004-4MGH

### Pump:

External bypass system allows more water into the system to protect from heat build-up ■ Forged brass manifold (Nickel plated brass on 4000-PSI models) ■ Thermal relief valve ■ Water filter with clear sleeve for screen inspection

### Frame:

Powder coated steel frame and base plate with 1¼-inch tube handles ■ Convenient gun/wand holder and hose wrap ■ Two-piece belt guard for quick access to belts ■ 13-inch flat-free tires

### Component:

Heavy-duty belt drive system

### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° ■ 50-foot x ¾-inch non-marking high pressure hose with quick connects ■ Professional-grade insulated trigger gun with safety lock-off

### Limited Warranties:

1 year Mi-T-M unloader (3500 and 4000-PSI models) ■ 3 year Honda and Vanguard engines ■ 10 year General pump

### Certification:

Intertek - Certified to UL-1776



CW-3504-5MGH

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH	2500	4.4	389cc Honda GX390 OHV	General	3-0202	Factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH	3000	3.5	389cc Honda GX390 OHV	General	3-0202	Factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH	3500	3.8	389cc Honda GX390 OHV	General	3-0203	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH	4000	3.5	389cc Honda GX390 OHV	General	3-0075	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MVO	4000	4.0	480cc Vanguard OHV, electric start - battery included	General	3-0075	Mi-T-M, factory preset	48in.	46x28x30in.	330 lb.	256 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	36-in. insulated dual lance	CW-2505-4MGH & CW-3004-4MGH
851-0338	50-ft. x ¾-in. non-marking high pressure hose	All models	CX-0045	Electric start - battery included	All Honda models
AW-8400-0021	Low pressure detergent injector	All models	CX-0054	Roll cage	All Honda models
			CX-0055	Roll cage	CW-4004-5MVO