

# Trash Pumps

## 3 and 4-Inch

### Frame:

Heavy-duty powder coated wraparound frame with 1-inch steel tubing ■ Rubber isolators minimize vibration

### Components:

Durable silicon carbide mechanical seals ■ Cast iron impeller and volute for reduced vibration and wear ■ Die cast aluminum pump is lightweight and portable ■ Easy-to-remove clean-out cover and volute for easy cleaning of debris

### Limited Warranties:

2 year pump ■ 3 year Honda engine

Remove unwanted water and waste quickly with these trash pumps. Available in two sizes, they can handle solids up to 1-inch in diameter. The die cast aluminum pump makes them lightweight, extremely durable and easy to transport.



WTP-T04-OMGH



WTP-T03-OMGH shown with 3-inch suction and discharge kit, 70-0525



WTP-T04-OMGH shown with wheel kit accessory, AW-5740-0017

	SUCTION									
MODEL NUMBER	DISCHARGE SIZE	MAX. TOTAL HEAD	SUCTION LIFT	DISPLACEMENT/ENGINE	PSI	MAX. CAPACITY	FUEL TANK CAPACITY	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-T03-OMGH	3in.x3in.	95ft.	26ft.	270cc Honda GX270 OHV	38	370 GPM	1.39 gallons	29x21.8x22.5in.	177 lb.	152 lb.
WTP-T04-OMGH	4in.x4in.	95ft.	26ft.	389cc Honda GX390 OHV	38	580 GPM	1.6 gallons	29x21.8x22.5in.	192 lb.	167 lb.

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
15-0294	20-ft. x 3-in. green PVC hard suction hose with fittings	WTP-T03-OMGH
15-0296	50-ft. x 3-in. blue PVC soft discharge hose	WTP-T03-OMGH
19-0629	3-in. steel suction strainer with round openings	WTP-T03-OMGH
70-0525	3-in. suction and discharge kit	WTP-T03-OMGH
AW-5740-0017	Wheel kit	All models
15-0356	20-ft. x 4-in. green PVC hard suction hose with fittings	WTP-T04-OMGH
15-0357	50-ft. x 4-in. blue PVC soft discharge hose	WTP-T04-OMGH
19-0277	4-in. steel suction strainer with round openings	WTP-T04-OMGH
70-0661	4-in. suction and discharge kit	WTP-T04-OMGH



Suction and discharge kit, 70-0661