

HS Series

Hot Water – Gasoline/Diesel – Belt Drive

Pump:

External bypass system allows more water into the system to protect from heat build-up ■ Factory preset unloader ■ Forged brass manifold ■ 80-mesh, high-volume, stainless-steel screen inlet water strainer

Engine:

Electric start - battery included

Frame:

Heavy-duty powder coated 1½-inch steel square tube frame

Components:

2900-watt generator ■ Heavy-duty dual cogged belt drive system ■ No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel) ■ ½-inch schedule 80-coil with stainless-steel wrap

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° ■ 50-foot x ¾-inch steel wire-braided high pressure hose with quick connects ■ Professional-grade insulated trigger gun with safety lock-off ■ Adjustable pressure insulated dual lance

Limited Warranties:

3 year coil ■ 3 year Honda, Kubota and Vanguard engines ■ 7 year AR and General pumps

Certification:

CSA Certified - US and Canada

The rugged skid frame of the HS Series makes it a great option for mounting on a water trailer, giving you the capability to clean dirt, oil and grime literally anywhere. It is designed to stand up to the harsh elements of industrial pressure washing.



HS-4005-OMDK



GASOLINE MODELS						ENGINE FUEL	BURNER FUEL	BURNER	BTU PER	DIMENSIONS		
MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	TANK CAPACITY	TANK CAP.	FUEL CONS.	HOUR	(LxWxH)	SHIP WT.	NET WT.
HS-3005-OMGV	3000	4.8	480cc Vanguard OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	816 lb.	710 lb.
HS-3505-1MGH	3500	4.7	688cc Honda GX630 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	854 lb.	750 lb.
HS-3506-1MGH	3500	5.6	688cc Honda GX630 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	50x34x46in.	864 lb.	760 lb.
HS-4004-1MAH*	4000	4.0	688cc Honda GX630 OHV	AR	3-0213	10.0 gallons	10.0 gallons	2.76 gph	386,400	50x34x46in.	854 lb.	750 lb.
DIESEL MODELS						ENGINE FUEL	BURNER FUEL	BURNER	BTU PER	DIMENSIONS		
MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	PUMP	Mi-T-M NO.	TANK CAPACITY	TANK CAP.	FUEL CONS.	HOUR	(LxWxH)	SHIP WT.	NET WT.
HS-3006-OMDK	3000	5.6	16.8 HP Kubota Z602 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.
HS-3505-OMDK	3500	4.7	16.8 HP Kubota Z602 OHV	General	3-0202	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.
HS-4005-OMDK*	4000	4.5	16.8 HP Kubota Z602 OHV	General	3-0262	10.0 gallons	10.0 gallons	3.37 gph	471,800	56.5x34x46in.	940 lb.	836 lb.

*Model equipped with trapping unloader, all other models equipped with K7 flow actuated unloader.

HS Series

Hot Water – Gasoline/Diesel – Belt Drive



AW-9000-0003 dual-axle trailer shown with HS-3505-1MGH hot water pressure washer and hose reel (available as accessories)

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
20-1070A18	Removable painted front panel	All models	HX-0140*	Steam combination 250°F	HS-3506-1MGH
20-1366A52	Black powder coated rain cap, octagonal	All models	HX-0141*	Steam combination 250°F	HS-3006-OMDK
50-0177	Stack adapter	All models	HX-0142	Steam combination 250°F	4000-PSI models
850-0324	Gasket (for 50-0177)	All models	HX-0143	Trapping unloader	HS-3006 & HS-3506 models
AW-5740-0000	Wheel kit	All models	HX-0144*	Dual gun	HS-3006 & HS-3506 models
AW-6000-1006	Hot water skid equipment cover	All models	HX-0145	Adjustable thermostat, 86°-248°F	All models
AW-8400-0021	Low pressure detergent injector	All models, except HS-3506 & HS-3006	HX-0146	Hour meter	All models
HX-0130	Three-way ball valve	All models	HX-0147	Four point lifting capability	All models
HX-0131	High pressure detergent injector, K7	3000 to 3500-PSI models	HX-0148*	Adjustable detergent valve	All models
HX-0133	Steam combination 250°F, K7	HS-3005 & HS-3505 models	HX-0200	Trapping unloader	HS-3005 & HS-3505 models
HX-0135	Steam combination 250°F, K7	HS-3506-1MGH	HX-0252	Pressure washer option for PWR-10-OME1 trailer-mount package	HS-3505-1MGH
HX-0136	Steam combination 250°F, K7	HS-3006-OMDK			
HX-0138*	Steam combination 250°F	HS-3005-OMGV			
HX-0139*	Steam combination 250°F	HS-3505 models			

***Requires trapping unloader.**
Note: To order options HX-0138 to HX-0141 or HX-0144 you must order option HX-0143 or HX-0200 (not required for 4000-PSI models, which already come equipped with trapping unloader).