8-GallonSingle Stage – Gasoline

Compressor Pump:

Splash lubricated
Stainless-steel braided discharge hose
Large canister intake filter
Oil level sight indicator

Frame:

Powder coated 8-gallon twin tank receivers ¶ %16-inch base plate to reduce vibration ¶ 16-gauge powder coated two-piece belt guard ¶ 10-inch flat-free tire

Components:

Regulator and two gauges for tank and outlet pressure
Manual drain valves for proper maintenance
12-inch fly wheel
Quality pilot valve unloader

Designed for maximum efficiency, contractors love the portability of this wheelbarrow style 8-gallon air compressor. It provides essential air power for tools around construction sites such as nailers, air hammers and impact wrenches.

Limited Warranties:

2 year pump exchange (see page 77 for more information) 3 year Honda and Kohler engines



MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH65-08M	13.9 @ 90	196cc Honda GX200 OHV	Single stage, cast iron	8-gallon	Pneumatic	44.5x18.5x27in.	200 lb.	175 lb.
AM1-PK07-08M	13.9 @ 90	208cc Kohler CH270 OHV	Single stage, cast iron	8-gallon	Cable throttle	44.5x18.5x27in.	200 lb.	175 lb.

Accessories & Options:

	!		
PART NUMBER	DESCRIPTION	FITS MODELS	
70-0357	Engine oil drain extension	All models	
854-0093	854-0093 Service mount truck kit - recommended for models that are mounted in service truck applications. You will also need to order stationary option, AX-0078.		
AW-6000-1002	Equipment cover	All models	
AX-0003	Manual drain/regulator/metal bowl	All models	
AX-0078	Stationary option	All models	