

30 & 80-Gallon / Base-Mount Two Stage – Gasoline

Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Engine:

Electric start - battery and cables not included

Frame:

- Powder coated ASME coded 30 or 80-gallon receiver tank (Tank-mounted models only)
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Removable base plate offers flexible installation

Components:

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- 16 1/2-inch fly wheel
- Tank drain valve
- Service truck mount kit (Standard on base-mount models only)

Limited Warranties:

- 1 year Mi-T-M engine
- 2 year pump exchange (see page 77 for more information)
- 3 year Honda and Kohler engines

Certifications:

- ASME Boiler and Pressure Vessel Code - UM (30-gallon models)
- ASME Boiler and Pressure Vessel Code - U (80-gallon models)

Ideal for commercial construction, industrial and automotive industries, the 30-gallon, 80-gallon and base-mount air compressors are designed to provide high capacity air flow. Mount one in a service truck and take it to the most demanding jobsite.



ABS-13H-B



ABS-14M-30H

TANK-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-30H	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	30-gallon	Pneumatic	38x23x46in.	480 lb.	416 lb.
ABS-14K-30H	29.0 @ 175	429cc Kohler CH440 OHV	Two stage, cast iron	30-gallon	Cable throttle	38x23x46in.	480 lb.	416 lb.
ABS-14M-30H	29.0 @ 175	420cc Mi-T-M OHV	Two stage, cast iron	30-gallon	Pneumatic	38x23x46in.	480 lb.	416 lb.
ABS-13H-80H	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.
ABS-14M-80H	29.0 @ 175	420cc Mi-T-M OHV	Two stage, cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.

BASE-MOUNTED MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-B	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.
ABS-14M-B	29.0 @ 175	420cc Mi-T-M OHV	Two stage, cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	30-gallon & base-mount models	IX-0055	Remote start/choke: 6-ft. wire extension for key switch	Honda models
AX-0077	Battery box and tray	30 & 80-gallon models	IX-0059	Remote start/choke: 6-ft. wire extension for key switch, sealed cable	Honda models
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use. Recommended for models that are mounted in service truck applications	30 & 80-gallon models			