

Rotary Screw

Single Stage – Gasoline

Compressor Pump:

Integrated air/oil separator ■ Integrated thermostatic bypass valve ■ Integrated oil filter ■ Banded 4 V-belt drive system ■ Easy-to-read oil level indicator ■ High oil temperature shutdown

Engine:

Electric start - battery and cables included ■ Low-oil level shutdown

Frame:

Powder coated steel frame with 1¼-inch roll cage, handle, 4-point lifting hook, winch point and tie-down anchors ■ 15-inch pneumatic tires

Components:

10½-gallon aluminized steel fuel tank ■ Oil cooler with guard ■ Pressure gauge ■ Ball valve controlled ¾-inch outlet ■ Adjustable pilot valve adjusts engine RPM based on air power needed

Limited Warranties:

3 year standard when RotorLub™ oil, filters and parts are used at the prescribed intervals ■ 3 year Kohler engine

Time is money and construction professionals demand products that will maximize production. This compact and portable rotary screw compressor not only produces a large volume of air for multiple tools, it is the only air compressor needed on large construction sites.



AR1-PK37-M

MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AR1-PK37-M	115 @ 100	999cc Kohler CH1000 OHV	Single stage, rotary screw	Pneumatic	50.75x30.5x43.5in.	770 lb.	698 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODEL
19-0278	Oil filter	AR1-PK37-M
19-0279	Air/oil separator	AR1-PK37-M
AW-2200-0001	Wye ball valve assembly	AR1-PK37-M
AW-2200-0002	Water separator assembly	AR1-PK37-M
AW-2200-0003	Pressure regulator assembly	AR1-PK37-M
AW-2200-0004	Champion RotorLub™ 8000, 5-gallon pail	AR1-PK37-M
AW-2200-0005	Champion RotorLub™ 8000, 1-gallon bottle	AR1-PK37-M
AX-0076	Skid feet	AR1-PK37-M