

# 8-Gallon Single Stage – Electric

### Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

### Motor:

- Auto start/stop - continuous run optional
- Thermal overload motor protection

### Frame:

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- 10-inch flat-free tire

### Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch
- Start/stop control set at 95 to 125-PSI (Not on continuous run models)

### Limited Warranties:

- 1 year electric motor
  - 2 year pump exchange
- (see page 77 for more information)

### Certification:

CSA Certified - US and Canada


A great choice for many jobsites, this popular 8-gallon electric air compressor features advanced technology and performance on any jobsite where electricity is available. Power everything from grinders to nail guns.



AM1-PE02-08M



AM1-PE15-08M



NEMA 5-15P, 15-amp plug  
NEMA 5-20P, 20-amp plug

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage, cast iron	8-gallon	NEMA 5-15P	44.5x18.5x25in.	190 lb.	170 lb.
AM1-PE02-08M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage, cast iron	8-gallon	NEMA 5-20P	44.5x18.5x25in.	203 lb.	183 lb.

### Accessory & Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models
AX-0002	Auto drain/regulator/plastic bowl	All models
AX-0003	Manual drain/regulator/metal bowl	All models
AX-0005	Dual control - continuous run & auto start/stop	All models
AX-0078	Stationary option	All models