30-Gallon

Two Stage - Diesel

Compressor Pump:

Splash lubricated
Stainless-steel braided discharge hose Large canister intake filter
Oil level sight indicator

Generator:

Brushless alternator ■ Total harmonic distortion (THD) less than 6% • 100% copper windings • Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

Engine:

Electric start - battery, box and cables not included
Glow plug equipped for easy starting in cold temperatures

Frame:

Powder coated ASME coded 30-gallon receiver tank 3/16-inch base plate to reduce vibration ■ 16-gauge powder coated two-piece belt guard

Components:

Regulator and two gauges for tank and outlet pressure Manual drain valves for proper maintenance ■ 16½-inch fly wheel - Quality pilot valve unloader

Limited Warranties:

2 year alternator • 2 year pump exchange (see page 77 for

Certification:

A reliable Kohler diesel engine powers this beast. Developed for the agricultural and construction industries, this model can take anything you throw at it. Mount it on the back of a service truck and take it to the most remote locations to get big jobs done.



KOHLER

				ALT	ERNATOR WATT	AGE						
C			CONT. WITH	CONT. WITH								
		CFM @	CFM @	MAX. AC	COMP.	COMP.				DIMENSIONS		
	MODEL NUMBER	90 PSI	175 PSI*	OUTPUT	ON-LOAD	OFF-LOAD	RECEPTACLES	HORSEPOWER/ENGINE	COMPRESSOR	(LxWxH)	SHIP WT.	NET WT.
	AG2-SKD9-30M	16.4	15.7	3000 watts	2300 watts	2750 watts	(2) NEMA 5-20R,	9.1 HP Kohler KD440 OHV	Two stage, cast iron	41x23x47in.	554 lb.	489 lb.
							(1) NEMA L6-20R		-			

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODEL	PART NUMBER	DESCRIPTION	FITS MODEL
70-0380	Engine oil drain extension	AG2-SKD9-30M	IX-0001	Vibration isolator pads - Isolators protect the unit	AG2-SKD9-30M
AW-6000-1002	Equipment cover	AG2-SKD9-30M		from vibration during use. Recommended for models	
AX-0070	Battery tray, box and 2-ft. of cables	AG2-SKD9-30M		that are mounted in service truck applications	