ChoreMaster[®] Series 3600, 6000 and 8000-Watt – Gasoline

The ChoreMaster Series generators feature a Mi-T-M OHV engine and are designed to provide maximum power for contractors and electrical back-up for power outages. This series is available in 3600, 6000 and 8000-wattage outputs.



Automatic Voltage Regulator

AVR regulates voltage for a stable output when adding or removing loads. Important in more sensitive equipment requirements.

MODEL NO.	GEN-3600-0MM0		
MAX. AC OUTPUT	3600 watts		
RATED AC OUTPUT	3000 watts		
DISPLACEMENT/ENGINE	212cc Mi-T-M OHV		
ALTERNATOR	Brushed 120V, 60Hz		
MAX. AMPS (120V/240V)	30.0		
CONT. AMPS (120V/240V)	25.0		
RECEPTACLES	(2) 120V, 20A GFCI duplex		
	(1) 120V, 30A twist lock		
CIRCUIT BREAKERS	(1) Main circuit breaker		
	(2) 20A circuit breakers, single pole		
	(1) 10A DC breaker		
RATED SPEED	3600 RPM		
DECIBEL RATING	72.0		
FUEL CAPACITY	4.0 gallons		
RUN TIME (AT FULL LOAD)	8.5 hours		
IDLE CONTROL	No		
WHEEL KIT	No		
DIMENSIONS (LxWxH)	24.9x17.6x17.9in.		
SHIP WT.	134 lb.		
NET WT.	102 lb.		



All Models

All Models

GEN-6000-0MM0

6000 watts 5500 watts 389cc Mi-T-M OHV Brushed 120V/240V, 60Hz 50.0/25.0 45.8/22.9 (2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) Main circuit breaker (2) 20A circuit breakers, single pole (1) 10A DC breaker 3600 RPM 74.0 6.6 gallons 6.5 hours Yes Yes, includes tires and rubber gripped handles 39.1x28.7x30.6in.* 228 lb. 180 lb.

Alternator:

Total harmonic distortion (THD) less than 6%
Copper and aluminum windings

Frame:

Low profile, compact design
Powder coated wraparound frame with 1-inch steel tubing

Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
Large low tone muffler
Engine on/off switch
Fuel shut-off valve
DC/battery charging

Limited Warranties:

1 year alternator = 1 year Mi-T-M engine

Certification:

CSA Certified



GEN-8000-0MME 8000 watts

7000 watts 420cc Mi-T-M OHV with electric start - battery included Brushed 120V/240V, 60Hz 66.6/33.3 58.3/29.2 (2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock (1) Main circuit breaker (2) 20A circuit breakers, single pole (1) 10A DC breaker 3600 RPM 74.0 6.6 gallons 6.0 hours Yes Yes, includes tires and rubber gripped handles 39.1x28.7x30.6in.* 237 lb. 195 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating. *Dimensions include the wheel kit with the handles in the down position.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models	AW-6000-1002	Equipment cover	6000 & 8000-watt models
AW-5090-0009	Lifting hook	GEN-3600-0MM0			