

Portable Generators

3000 and 5000-Watt – Gasoline

Alternator:

Total harmonic distortion (THD) less than 5% ■ 100% copper windings

Frame:

Heavy-duty powder coated wraparound frame with 1-inch steel tubing ■ Angled isolator design features four neoprene isolators

Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles ■ Large low tone muffler ■ Fuel shut-off valve ■ Easy-to-read fuel gauge ■ Heavy-duty industrial air cleaner

Miscellaneous:

USDA/USFS-approved spark arrestors

Limited Warranties:

2 year alternator ■ 3 year Honda and Kohler engines


Certification:

CSA Certified

Designed with contractors in mind, the 3000-watt and 5000-watt generators are perfect for powering a multitude of tools on any jobsite. This series also features long run times so you won't need to take a refuel break as often.



GEN-3000-1MH0



MODEL NO.	GEN-3000-1MH0	GEN-3000-1MK0	GEN-5000-0MH0	GEN-5000-0MK0
MAX. AC OUTPUT	3000 watts	3000 watts	5000 watts	5000 watts
RATED AC OUTPUT	2450 watts	2450 watts	4400 watts	4400 watts
DISPLACEMENT/ENGINE	163cc Honda GX160 OHV	208cc Kohler CH270 OHV	270cc Honda GX270 OHV	277cc Kohler CH395 OHV
ALTERNATOR	Brushless 120V, 60Hz	Brushless 120V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	25.0	25.0	41.7/20.8	41.7/20.8
CONT. AMPS (120V/240V)	20.4	20.4	36.7/18.3	36.7/18.3
RECEPTACLES	(1) 120V, 20A GFCI duplex	(1) 120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock
CIRCUIT BREAKERS	(1) 20A push-button	(1) 20A push-button	(1) 120V, 30A twist lock (2) 20A toggle circuit breakers, single pole	(1) 120V, 30A twist lock (2) 20A toggle circuit breakers, single pole
RATED SPEED	3600 RPM	3600 RPM	(1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
DECIBEL RATING	74.8	74.8	3600 RPM	3600 RPM
FUEL CAPACITY	2.6 gallons	2.6 gallons	73.8	73.8
RUN TIME (AT FULL LOAD)	7.4 hours	7.4 hours	5.7 gallons	5.7 gallons
FULL POWER SWITCH	No	No	6.8 hours	6.8 hours
DIMENSIONS (LxWxH)	25x18x18in.	25x18x18in.	Yes	Yes
SHIP WT.	146 lb.	146 lb.	29x19.75x22.5in.	29x19.75x22.5in.
NET WT.	130 lb.	130 lb.	198 lb.	198 lb.
			176 lb.	176 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	5000-watt models	AW-5740-0009	Wheel kit with flat-free tires	5000-watt models
AW-5090-0003	Lifting hook	5000-watt models	GX-0004	Hour meter	5000-watt models