

Portable Generators

6000, 7500 and 8000-Watt – Gasoline

You can have power all day long with the durable 6000-watt, 7500-watt and 8000-watt generators from Mi-T-M. Ideal for jobsites where electric power isn't readily available you can run multiple tools with quality power.



GEN-8000-0MKE



GFCI 5-20R
All Models



NEMA L14-20R
120V/240V
GEN-6000
Models



NEMA L14-30R
120V/240V
GEN-7500 &
8000 Models



NEMA L5-30R
120VAC
All Models

Alternator:

Total harmonic distortion (THD) less than 5% ■ 100% copper windings

Frame:

Heavy-duty powder coated wraparound frame with 1-inch steel tubing ■ Angled isolator design features four neoprene isolators

Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles ■ Large low tone muffler ■ Fuel shut-off valve ■ Easy-to-read fuel gauge ■ Idle control ■ Voltmeter/hour meter ■ Heavy-duty industrial air cleaner

Miscellaneous:

USDA/USFS-approved spark arrestors

Limited Warranties:

2 year alternator ■ 3 year Honda and Kohler engines

Certification:

CSA Certified



GEN-6000-0MHO

MODEL NO.	GEN-6000-0MHO / GEN-6000-0MHE / GEN-6000-0MKO
MAX. AC OUTPUT	6000 watts
RATED AC OUTPUT	5000 watts
DISPLACEMENT/ENGINE	389cc Honda GX390 OHV / 389cc Honda GX390 OHV with electric start - battery included / 429cc Kohler CH440 OHV
ALTERNATOR	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	50.0/25.0
CONT. AMPS (120V/240V)	41.7/20.8
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole
RATED SPEED	3600 RPM
DECIBEL RATING	77.1
FUEL CAPACITY	7.3 gallons
RUN TIME (AT FULL LOAD)	8.0 hours
DIMENSIONS (LxWxH)	29x24.4x22.5in.
SHIP WT.	232 lb. / 240 lb. / 232 lb.
NET WT.	210 lb. / 218 lb. / 210 lb.

GEN-7500-0MHO / GEN-7500-0MHE
7500 watts
6500 watts
389cc Honda GX390 OHV / 389cc Honda GX390 OHV with electric start - battery included
Brushless 120V/240V, 60Hz
62.5/31.3
54.2/27.1
(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
3600 RPM
80.0
7.3 gallons
6.9 hours
29x24.4x22.5in.
255 lb. / 263 lb.
233 lb. / 241 lb.

GEN-8000-0MKO / GEN-8000-0MKE
8000 watts
6900 watts
429cc Kohler CH440 OHV / 429cc Kohler CH440 OHV with electric start - battery included
Brushless 120V/240V, 60Hz
66.7/33.3
57.5/28.8
(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
3600 RPM
78.2
7.3 gallons
6.9 hours
29x24.4x22.5in.
255 lb. / 259 lb.
233 lb. / 237 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models	AW-5740-0010	Wheel kit with flat-free tires	All models
AW-5090-0004	Lifting hook	All models	AW-6000-1002	Equipment cover	All models