# Portable Generators

# 14000-Watt - Gasoline

### Alternator:

Total harmonic distortion (THD) less than 5% ■ 100% copper windings

# Frame:

Reinforced powder coated 11/4-inch steel tube frame 13-inch flat-free tires

# Components:

Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles 
Large low tone muffler ■ Easy-to-read fuel gauge ■ Idle control ■ Voltmeter/ hour meter Heavy-duty industrial air cleaner

#### Miscellaneous:

USDA/USFS-approved spark arrestors

### Limited Warranties:

2 year alternator 

3 year Honda engine

#### Certification:

CSA Certified



Built for industrial applications yet with the portability to move from one job to the next, this generator will never let you down. It's a virtual power plant and is the perfect tool for professional contractors and rental customers.



MODEL NO. MAX. AC OUTPUT

RATED AC OUTPUT DISPLACEMENT/ENGINE

ALTERNATOR MAX. AMPS (120V/240V) CONT. AMPS (120V/240V)

RECEPTACLES

CIRCUIT BREAKERS

RATED SPEED DECIBEL RATING FUEL CAPACITY

RUN TIME (AT FULL LOAD) DIMENSIONS (LxWxH) SHIP WT. NET WT.

GEN-14000-1MHE

14000 watts

12000 watts

688cc Honda GX630 OHV with electric start - battery included

Brushless 120V/240V, 60Hz

116.7/58.3 100.0/50.0

(2) 120V, 20A GFCI duplex / (1) 120V, 30A twist lock

(1) 120V/240V, 30A twist lock / (1) 120V/240V, 50A

(2) 20A toggle circuit breakers single pole (1) 30A toggle circuit breaker, single pole

(1) 30A toggle circuit breaker, double pole (1) 50A toggle circuit breaker, double pole

3600 RPM 77.5 13.2 gallons 8.0 hours

31.5x30.5x37.5in. 568 lb.

508 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

## Accessories & Options:











GX-0005 option CS6369A 50A twist lock receptacle