

An Employee Owned Company

8-Gallon

Industrial Single Stage - Electric

The 8-gallon electric air compressors offer versatility for both large and small jobs. They're ideal for many uses.



COMPRESSOR PUMP

- · Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

MOTOR

- Auto start/stop
- Thermal overload motor protection
- 8-foot power cord

FRAME

- · Powder coated twin tank receivers
- 3/16-inch base plate to reduce vibration
- · Powder coated two-piece belt guard
- 10-inch flat-free tire

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch
- Start/stop control set at 95 to 125-PSI (Not on continuous run models)

LIMITED WARRANTY

1 year electric motor

CERTIFICATION

• ETL Certified – US and Canada

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08M	7.3 @ 90	1.5 HP, 120V, 13.2A	NEMA 5-15P	44.5x18.5x25in.	190 lb.	170 lb.
AM1-PE02-08M	8.2 @ 90	2.0 HP, 120V, 18.8A	NEMA 5-20P	44.5x18.5x25in.	203 lb.	183 lb.

ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	All models

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0002	Auto drain/regulator/plastic bowl – Drains moisture from air system	All models
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0005	Dual control – Compressor can be operated in start/stop mode or continuous run where pilot valve exhausts air to atmosphere	All models
AX-0078	Stationary option – Converts the portable model to a stationary model, removes the wheel and handles	All models





20-amp plug





WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.