

### 8-Gallon

### Air Compressors



This wheelbarrow style, versatile unit is perfect for new construction, remodeling and shop projects. It can be used to power a variety of air tools including paint sprayers and pneumatic drills.

#### COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- · Oil level sight indicator

#### FRAME

- · Powder coated twin tank receivers
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- 10-inch flat-free tires
- Reinforced frame designed to withstand jobs requiring heavy use (AM2-PH09-08M2)
- Enhanced pilot valve exhaust filter (AM2-PH09-08M2)

#### COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- · Quality pilot valve unloader

#### LIMITED WARRANTY

• 3 year engine



# 8-Gallon

## Air Compressors – Two Stage – Gasoline

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WODEL NOWBER	011416101	DIGI EAGENIENT/ENGINE	ENGINE IDEE CONTINUE	DIMENSIONS (EXTENT)	Orni Wi.	1421 ***1.
AM2-PH09-08M	17.2 @ 175	270cc Honda GX270 OHV+	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PH09-08ME^	17.2 @ 175	270cc Honda GX270 OHV+	Pneumatic	44x26x31in.	337 lb.	267 lb.
AM2-PH09-08M2	17.2 @ 175	270cc Honda GX270 OHV+	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler CH395 OHV	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PM09-08M	17.2 @ 175	300cc Mi-T-M OHV	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PM09-08ME^	17.2 @ 175	300cc Mi-T-M OHV	Cable throttle	44x26x31in.	337 lb.	267 lb.

<sup>\*</sup>Equipped with 150-PSI maximum rated regulator.

#### ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	<b>Equipment cover</b> – Keeps your equipment clean, dry and looking like new	All models

#### OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0084	Stationary option – Converts the portable model to a stationary model, removes the tire and handles	All models except AM2-PH09-08M2
IX-0055	Remote start/choke – 7-foot wire extension for key switch	AM2-PH09-08ME
IX-0059	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PH09-08ME
IX-0067	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-PM09-08ME



<sup>+49</sup> state engine. Not for sale in California.

 $<sup>{}^{\</sup>wedge}\textit{Equipped with electric start-battery, box and cables not included}.$