



An  
Employee  
Owned  
Company

# CA Aluminum Series

Industrial Cold Water  
Pressure Washers

*Gasoline — Portable — Direct Drive*



CA-4004-1MGM

*Contractors choose the CA Aluminum Series for power and portability. This series is equipped with a corrosion-resistant aluminum frame and patented vibration plate for added durability.*

#### PUMP

- Equipped with Mi-T-M Pressure Relief Start
- External bypass system protects from heat build-up (CAT and General pump models)
- Forged brass manifold
- Thermal relief valve
- In-line water strainer

#### FRAME

- Corrosion-resistant aluminum frame
- Patented vibration isolation plate
- 13-inch flat-free tires (10-inch tires on CA-2403, CA-2703 and CA-3003 models)

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15° and 25°
- 50-foot x 3/8-inch non-marking hose
- Insulated trigger gun

#### LIMITED WARRANTIES

- 1 year Mi-T-M unloader
- 3 year Honda, Kohler, Mi-T-M and Vanguard engines
- 7 year AR, CAT, General and Mi-T-M pumps

#### CERTIFICATION

- ETL Certified – US (Select models, see chart)



# CA Aluminum Series

## Cold Water – Gasoline – Portable – Direct Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CA-2403-1MMH*	2400	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMH*	2700	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMK*	2700	2.4	208cc Kohler CH270 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMM	2700	2.4	212cc Mi-T-M OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMV	2700	2.4	203cc Vanguard OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-3003-1MAH*	3000	3.0	270cc Honda GX270 OHV+	AR	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAK*	3000	3.0	277cc Kohler CH395 OHV	AR	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAM	3000	3.0	300cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3504-1MAH*	3500	3.5	389cc Honda GX390 OHV+	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MAK	3500	3.5	429cc Kohler CH440 OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MAM	3500	3.5	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MGH*	3500	4.0	389cc Honda GX390 OHV+	General	Adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAH*	4000	3.5	389cc Honda GX390 OHV+	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAK*	4000	3.5	429cc Kohler CH440 OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAM	4000	3.5	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAV	4000	3.5	408cc Vanguard OHV	AR	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MCH*	4000	4.0	389cc Honda GX390 OHV+	CAT	Adjustable pressure	48in.	42.5x23.5x24.5in.	178 lb.	128 lb.
CA-4004-1MCM	4000	4.0	420cc Mi-T-M OHV	CAT	Adjustable pressure	48in.	42.5x23.5x24.5in.	178 lb.	128 lb.
CA-4004-1MGH*	4000	4.0	389cc Honda GX390 OHV+	General	Adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MGM	4000	4.0	420cc Mi-T-M OHV	General	Adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

\*49 state fuel tank. Not for sale in California.

\*ETL Certified – US.

### ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/8-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0097	External bypass system – Allows more water into the system to protect from heat build-up	2400 to 2700-PSI models
CX-0099	External bypass system – Allows more water into the system to protect from heat build-up	3000-PSI models
CX-0098	External bypass system – Allows more water into the system to protect from heat build-up	3500 to 4000-PSI AR pump models

 **WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.**