

An **Employee** Owned Company

# **CAW Aluminum Series**

Electric - Direct Drive Wall-Mount

Mount these CAW Series pressure washers inside wash bays, workshops and garages to clean vehicles and equipment.



- · Stainless-steel and brass trapping unloader
- Factory preset unloader
- Forged brass manifold
- Thermal relief valve
- · External quick connect low pressure detergent injector
- Pump accepts incoming water up to 165°F (175°F on CAW-4004-0ME1)

#### **MOTOR**

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 4-foot power cord

#### FRAME

· Aluminum frame with wall-mounting brackets



## COMPONENTS

- Time delay shutdown
- Remote-mounted electrical box, must be within 3½-feet of unit

#### **UNIT INCLUDES**

- Quick connect nozzles 0°, 15°, 25° and 40°
- 50-foot x %-inch non-marking hose
- 36-inch adjustable dual lance with insulated trigger gun (48-inch on CAW-4004-0ME1)

## LIMITED WARRANTIES

- · 1 year electric motor
- 7 year pump

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)^	SHIP WT.	NET WT.
CAW-2004-0ME1	2000	3.9	6.0 HP, 230V, 1Ø, 24.1A	General	NEMA 6-30P	34x17.25x18in.	248 lb.	188 lb.
CAW-2004-0ME3*	2000	3.9	6.0 HP, 230V, 3Ø, 17.3A or 6.0 HP, 460V, 3Ø, 8.64A	General	NEMA L15-20P	34x17.25x18in.	223 lb.	163 lb.
CAW-3004-0ME1	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	NEMA 6-50P	34x17.25x18in.	268 lb.	208 lb.
CAW-3004-0ME3*	3000	3.9	8.0 HP, 230V, 3Ø, 22.8A or 8.0 HP, 460V, 3Ø, 11.4A	General	NEMA L15-30P	34x17.25x18in.	253 lb.	193 lb.
CAW-4004-0ME1	4000	4.0	10.0 HP, 230V, 1Ø, 40.8A	General	NEMA 6-50P	34x19x19in.	368 lb.	293 lb.

<sup>\*460</sup>V motors available as options. ^Dimensions do not include the mounting brackets.

# ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x %-inch non-marking hose – For when you need extra hose for added mobility	All models

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0078	Remote box – Adds control box, may be mounted away from unit to control on/off	All models
CX-0109	Additional remotes, up to 3 qty. – Additional remotes that may be added to unit after the first remote is installed; requires remote box option CX-0078	All models
CX-0110	460V on 6.0-HP, 3Ø model – When 460V of power is available	CAW-2004-0ME3
CX-0111	460V on 8.0-HP, 3Ø model – When 460V of power is available	CAW-3004-0ME3
CX-0112	Auto start/stop – When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models
CX-0133	4-foot power cord with GFCI — Replaces the standard 4-foot power cord	CAW-3004-0ME1







30-amp plug

NEMA L15-30P, NEMA 6-30P,



30-amp plug



50-amp plug

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

