



An
Employee
Owned
Company

CBA Aluminum Series

Gasoline — Belt Drive
Portable

The industrial and lightweight CBA Series pressure washer delivers the cleaning power needed for tough grime and peeling paint.



CBA-4004-1MCK

PUMP

- Equipped with Mi-T-M Pressure Relief Start
- External bypass system protects from heat build-up (CAT and General pump models)
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

FRAME

- Corrosion-resistant aluminum frame
- Patented vibration isolation plate
- Two-piece belt guard
- 13-inch flat-free tires

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking hose
- Insulated trigger gun

LIMITED WARRANTIES

- 1 year unloader
- 3 year engine
- 7 year pump

CERTIFICATION

- ETL Certified – US (Select models, see chart)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CBA-3504-1MAH*	3500	3.7	389cc Honda GX390 OHV*	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-3504-1MAK*	3500	3.7	429cc Kohler CH440 OHV*	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-3504-1MAM	3500	3.7	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-3504-1MGH*	3500	4.0	389cc Honda GX390 OHV*	General	Adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-4004-1MAH*	4000	3.4	389cc Honda GX390 OHV*	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-4004-1MAK*	4000	3.4	429cc Kohler CH440 OHV*	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-4004-1MAM	4000	3.4	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-4004-1MCH*	4000	3.7	389cc Honda GX390 OHV*	CAT	Adjustable pressure	48in.	47x27.5x28.5in.	206 lb.	156 lb.
CBA-4004-1MCK	4000	3.7	429cc Kohler CH440 OHV*	CAT	Adjustable pressure	48in.	47x27.5x28.5in.	206 lb.	156 lb.
CBA-4004-1MCM	4000	3.7	420cc Mi-T-M OHV	CAT	Adjustable pressure	48in.	47x27.5x28.5in.	206 lb.	156 lb.
CBA-4004-1MGH*	4000	4.0	389cc Honda GX390 OHV*	General	Adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.
CBA-4004-1MGM	4000	4.0	420cc Mi-T-M OHV	General	Adjustable pressure	48in.	47x27.5x28.5in.	215 lb.	165 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

*49 state fuel tank. Not for sale in California. *ETL Certified – US.

CBA Aluminum Series

Cold Water – Gasoline – Belt Drive – Portable

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

OPTION: *Option must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0082	External bypass system – Allows more water into the system to protect from heat build-up	AR pump models



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.