Mi-T-M® CORPORATION

An Employee Owned Company



CSW-0311-0MCME

CSW Series

Gasoline — Direct Drive Base-Mount

Soft wash units safely clean roofs, siding, decks, patios and fences using low-pressure and high-volume to remove tough stains, mildew and more.

PUMP
- High-performance Buna diaphragm pump
- Corrosion and chemical-resistant with polypropylene manifold
- Self-priming
- ¾" solid shaft gearbox

FRAME
- Powder coated aluminum frame for extra chemical resistance
- Rubber isolators for reduced vibration
- Designed to mount on truck or trailer
- Stainless-steel hardware

LIMITED WARRANTIES
- Engine and pump

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	FUEL TANK CAPACITY	UNIT DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CSW-0311-0MCH	300	11.0	196cc Honda GX200 OHV+	Comet	Comet, adjustable pressure	0.95 gallon	27x18x18in.	125 lb.	85 lb.
CSW-0311-0MCHE ϟ	300	11.0	196cc Honda GX200 OHV+	Comet	Comet, adjustable pressure	0.95 gallon	27x18x18in.	130 lb.	90 lb.
CSW-0311-0MCM	300	11.0	212cc Mi-T-M OHV	Comet	Comet, adjustable pressure	0.95 gallon	27x18x18in.	125 lb.	85 lb.
CSW-0311-0MCME ϟ	300	11.0	212cc Mi-T-M OHV	Comet	Comet, adjustable pressure	0.95 gallon	27x18x18in.	130 lb.	90 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.
+49 state fuel tank. Not for sale in California.
ϟEquipped with electric start – battery not included.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
15-0411	250-ft. x ⅝-in. soft wash hose – Heavy-duty hose designed for durability, flexibility and dependable performance, 300-PSI rated, ½-inch NPT fittings, with fixed and swivel end connections	All models
16-0501	Soft wash gun – Designed for longevity, comfort and control, easy-pull trigger, 2175-PSI rate, 21.0 GPM, ½-inch FPT inlet x ½-inch NPT outlet	All models
AW-0016-0501	Soft wash gun with lance – Includes soft wash gun with 12-inch lance, ½-inch NPT inlet and ¼-inch quick connect outlet	All models
16-0502	Wash down gun – Designed for efficient rinse down and general wash applications, 350-PSI rated, 16.0 GPM, ½-inch inlet	All models
18-1300	J-rod nozzle assembly – Provides fast, convenient nozzle changes, set of 4 nozzles in j-rod adapter, 0°, 15°, 25° and 40°, 30.0 orifice size	All models

Made in USA with Globally Sourced Components

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.