



An  
Employee  
Owned  
Company

## CW Premium Series

Gasoline — Belt Drive  
Portable

These durable “workhorse” pressure washers are built for blasting away mud, muck, dirt and grime from most any surface.

### PUMP

- External bypass system protects from heat build-up
- Forged brass manifold (Nickel plated brass on CW-4004 models)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### FRAME

- Powder coated steel frame
- Two-piece belt guard
- 13-inch flat-free tires

### COMPONENT

- Heavy-duty belt drive system

## Industrial Cold Water Pressure Washers



CW-3004-4MGH

### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking hose
- Insulated trigger gun

### LIMITED WARRANTIES

- 1 year unloader
- 3 year engine
- 7 year pump

### CERTIFICATION

- ETL Certified – US (Select models, see chart)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH*	2500	4.4	389cc Honda GX390 OHV+	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-2505-4MGK	2500	4.4	429cc Kohler CH440 OHV+	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-2505-4MGM	2500	4.4	420cc Mi-T-M OHV	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH*	3000	3.9	389cc Honda GX390 OHV+	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGK	3000	3.9	429cc Kohler CH440 OHV+	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGM	3000	3.9	420cc Mi-T-M OHV	General	Mi-T-M, factory preset	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH*	3500	3.8	389cc Honda GX390 OHV+	General	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGK	3500	3.8	429cc Kohler CH440 OHV+	General	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-3504-5MGM	3500	3.8	420cc Mi-T-M OHV	General	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH*	4000	3.5	389cc Honda GX390 OHV+	General	Mi-T-M, factory preset	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MVO*	4000	4.0	480cc Vanguard OHV+ with electric start – sealed battery included	General	Mi-T-M, factory preset	48in.	46x28x30in.	330 lb.	256 lb.

*Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.*

*\*49 state engine. Not for sale in California.      \*ETL Certified – US.*



# CW Premium Series

## Cold Water – Gasoline – Belt Drive – Portable

### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/4-inch non-marking hose – High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

### OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	CW-2505 & CW-3004 models
CX-0045	Electric start – sealed battery included	All Honda engine models
CX-0054	Roll cage – Designed to protect equipment, comes with a lifting hook, 1 1/4-inch powder coated steel tubing	All Honda, Kohler and Mi-T-M engine models
CX-0055	Roll cage – Designed to protect equipment, comes with a lifting hook, 1 1/4-inch powder coated steel tubing	CW-4004-5MVO



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).