



An
Employee
Owned
Company

ChoreMaster® Series 3600-Watt up to 8000-Watt Portable Gasoline Generators



GEN-6500-0MM1

The ChoreMaster generators are designed to provide maximum power for contractors and electrical backup for power outages.

EQUIPPED WITH
CO DETECTOR

ALTERNATOR

- Copper and aluminum windings (Copper windings on GEN-8000 model)

ENGINE

- Recoil start (GEN-8000 model also has electric start – sealed battery included)

FRAME

- Powder coated wraparound frame
- Handle, wheels and outlet covers (GEN-6500 and GEN-8000 models)

COMPONENTS

- Fuel shut-off valve
- DC/battery charging (GEN-3600 model)
- Equipped with CO detector with automatic shutdown (GEN-6500 and GEN-8000 models)
- Idle control (GEN-6500 and GEN-8000 models)
- Digital display for voltage, hertz, run hours and total hours (GEN-6500 and GEN-8000 models)
- USDA/USFS-approved spark arrestors

LIMITED WARRANTIES

- 1 year alternator
- 3 year engine

CERTIFICATION

- CSA Certified


ChoreMaster® 3600-Watt up to 8000-Watt Portable Gasoline Generators

USAGE	COMMERCIAL	COMMERCIAL	COMMERCIAL
MODEL NUMBER	GEN-3600-0MM0	GEN-6500-0MM1	GEN-8000-0MM1E
MAX. AC OUTPUT	3600 watts	6500 watts	8000 watts
RATED AC OUTPUT	3000 watts	6500 watts	7200 watts
DISPLACEMENT/ENGINE	212cc Mi-T-M OHV	420cc Mi-T-M OHV	420cc Mi-T-M OHV
ALTERNATOR	Brushed 120V, 60Hz	Brushed 120V/240V, 60Hz	Brushed 120V/240V, 60Hz
MAX. AMPS (120V/240V)	30.0	54.1/27.0	66.6/33.3
CONT. AMPS (120V/240V)	25.0	54.1/27.0	60.0/30.0
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 12V DC 8.3A	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole (1) 10A DC breaker	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	72.0	80.0	85.0
FUEL CAPACITY	4.0 gallons	7.53 gallons	7.53 gallons
RUN TIME (AT FULL LOAD)	8.5 hours	8.8 hours	6.5 hours
DIMENSIONS (LxWxH)	24.9x17.6x17.9in.	27.8x20.2x21.6in.	27.8x20.2x21.6in.
SHIP WT.	134 lb.	210 lb.	218 lb.
NET WT.	102 lb.	183 lb.	192 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-5090-0009	Lifting hook – For easier portability, folds down and out of the way when not in use	GEN-3600-0MM0
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	GEN-6500-0MM1 & GEN-8000-0MM1E



GFCI 5-20R
All Models



NEMA L5-30R
120VAC
All Models



NEMA L14-30R
120V/240V
GEN-6500 &
GEN-8000
Models



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.