



ChoreMaster® Series 4000-Watt up to 10000-Watt Portable Gasoline Generators



GEN-6500-0MM1

The ChoreMaster Series of generators come with a Mi-T-M OHV engine, is equipped with CO detection and designed to provide maximum power for contractors and back-up for power outages.

EQUIPPED WITH
CO DETECTOR

ALTERNATOR

- Copper windings (Copper and aluminum windings on GEN-4000 and GEN-6500 models)

ENGINE

- Recoil start (GEN-8000 and GEN-10000 also have electric start – sealed battery included)

FRAME

- Easy to remove access panels for spark plug, oil and air cleaner
- Handle and wheels
- Outlet covers

COMPONENTS

- Equipped with CO detector
- Automatic shutdown
- Fuel shut-off valve
- Idle control (GEN-6500, GEN-8000 and GEN-10000 models)
- Digital display for voltage, hertz, run hours and total hours
- USDA/USFS-approved spark arrestors

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- CSA Certified (GEN-6500 and GEN-8000 models)
- Intertek Certified to UL-1776 – Canada (GEN-10000-0MM1E)

ChoreMaster® 4000-Watt up to 8000-Watt Portable Gasoline Generators

USAGE	COMMERCIAL	COMMERCIAL	COMMERCIAL	COMMERCIAL
MODEL NUMBER	GEN-4000-0MM1	GEN-6500-0MM1	GEN-8000-0MM1E	GEN-10000-0MM1E
MAX. AC OUTPUT	4000 watts	6500 watts	8000 watts	10000 watts
RATED AC OUTPUT	3500 watts	6500 watts	7200 watts	9000 watts
DISPLACEMENT/ENGINE	224cc Mi-T-M OHV	420cc Mi-T-M OHV	420cc Mi-T-M OHV	500cc Mi-T-M OHV
ALTERNATOR	Brushed 120V, 60Hz	Brushed 120V/240V, 60Hz	Brushed 120V/240V, 60Hz	Brushed 120V/240V, 60Hz
MAX. AMPS (120V/240V)	31.7	59.2/29.6	66.6/33.3	83.3/41.7
CONT. AMPS (120V/240V)	29.2	54.0/27.0	60.0/30.0	75.0/37.5
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole	(2) 20A toggle circuit breakers, single pole (2) 30A toggle circuit breakers, single pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	68.0	80.0	85.0	82.9
FUEL CAPACITY	4.23 gallons	7.53 gallons	7.53 gallons	7.1 gallons
RUN TIME (AT FULL LOAD)	8.5 hours	8.8 hours	6.5 hours	5.5 hours
DIMENSIONS (LxWxH)	23.4x17.9x19.9in.	27.8x20.2x21.6in.	27.8x20.2x21.6in.	39.1x28.7x30.6in.
SHIP WT.	139 lb.	210 lb.	218 lb.	235 lb.
NET WT.	117 lb.	183 lb.	192 lb.	209 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter – 30A/125V female/male. Use to connect RV cordsets to 30A generators.	All models
32-1289	Triple receptacle adapter – Converts (1) L5-30 plug to (3) lighted 5-20 locking receptacles	All models
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new	All models



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.