

Propane/Natural Gas Directional

Available in both propane and natural gas, the Elite Series directional heaters are ductable and great for large or small area applications. Providing worry-free heating or air circulation for wide areas, the Elite Series portable heaters are perfect for tents, party applications and construction sites.

Frame:

- Durable powder coated outer casing and side lifting handles

Components:

- Thermostat control with 20-foot cord
- 15-foot hose and regulator assembly
- Independent fan and burner controls for simple operation
- Totally enclosed flame
- Electronic ignition
- Operates as a fresh air circulator or a heater

Limited Warranty:

- 1 year

Certifications:

- Warnock Hersey Mark

Important Notes:

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Extremely hot during operation. Keep children, animals and all combustible objects away from heater.



MH-0175-OMDH shown with duct diffuser, 68-5003

Elite Series – 85,000 up to 355,000 BTU

MODEL NO.	MH-0085-OMDH	MH-0175-OMDH	MH-0355-OMDH [^]	MH-0355-CMDH ^{^*}
HEAT OUTPUT	85,000 BTU	175,000 BTU	355,000 BTU	320,000 BTU
HOT-AIR FLOW	750 CFM	1,200 CFM	2,600 CFM	2,600 CFM
FUEL	Propane	Propane	Propane / Natural Gas	Propane / Natural Gas
FUEL CONSUMPTION	4.25 lb./hr.	8.75 lb./hr.	16.2 lb./hr. / 350 cu. ft./hr.	16.2 lb./hr. / 350 cu. ft./hr.
ELECTRICAL REQUIREMENTS	115V, 60Hz, 1Ø	115V, 60Hz, 1Ø	115V, 60Hz, 1Ø	115V, 60Hz, 1Ø
AMPS (STARTING/CONT.)	8.2/2.3 Amps	8.4/3.6 Amps	21.0/9.0 Amps	21.0/9.0 Amps
SUGGESTED TANK SIZE	100 lb.	100 lb.	200 lb.	200 lb.
INLET GAS PRESSURE	11in. WC	11in. WC	11in. WC - propane / 8.5in. WC - natural gas	11in. WC - propane / 8.5in. WC - natural gas
TEMP. RISE (ABOVE AMBIENT)	140°F	140°F	190°F - propane / 170°F - natural gas	190°F - propane / 170°F - natural gas
DUAL-FUEL HEATER	No	No	Yes, natural gas and propane	Yes, natural gas and propane
DIMENSIONS (LxWxH)	30x16x22in.	30.62x18.25x31.12in.	46x32.5x42in.	46x32.5x42in.
SHIP WT.	135 lb.	193 lb.	350 lb.	350 lb.
NET WT.	122 lb.	164 lb.	317 lb.	317 lb.

[^]Natural gas regulator is required to run heater on natural gas, for gas supply pressures between 1/2 and 5 lb. of pressure (Part #68-5009). Available as an accessory.

^{*}Model available in Canada only.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
68-5001	12-in. duct adapter - required to attach ducting to the heater	MH-0085 & MH-0175	68-5007	18-in. duct adapter - required to attach ducting to the heater	MH-0355
68-5002	Duct diffuser	MH-0085 & MH-0175	68-5008	Thermostat kit - replacement only	All models
68-5003	Heat diffuser	MH-0175	68-5009	Natural gas regulator	MH-0355
68-5004	Heat diffuser	MH-0085	68-5010	Two cylinder manifold	All models
68-5005	12-ft. x 12-in. white flexible air ducting; max. size	MH-0085 & MH-0175	68-5012	Duct diffuser	MH-0355
68-5006	12-ft. x 18-in. white flexible air ducting; max. size	MH-0355			