



An
Employee
Owned
Company

Gas-Fired Convection

Industrial
30,000 up to 200,000 BTU

These gas-fired convection heaters are quiet, portable and effective. Warm up a ventilated shop or garage efficiently.



MH-0080-CM11

FRAME

- Quick assembly two-piece burn chamber
- Durable steel housing
- Inner windshield protects burner flame from being extinguished

HEAT OUTPUT

- Variable heat settings
- 360° heat radius for even heating

COMPONENTS

- Matchless piezo spark ignition
- Automatic shut-off if flame is extinguished
- 15-foot hose and regulator

LIMITED WARRANTY

- 1 year

CERTIFICATIONS

- CSA Certified – US and Canada
- CSA Blue Star Certified – US
- CSA Blue Flame Certified – Canada

IMPORTANT NOTES

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Extremely hot during operation. Keep children, animals and all combustible objects away from heater.

MODEL NUMBER	MH-0080-CM11	MH-0200-CM11
HEAT OUTPUT	30-80,000 BTU	75-200,000 BTU
IGNITION TYPE	Push-button	Push-button
FUEL CONSUMPTION	1.4 / 3.7 lb./hr.	3.5 / 9.3 lb./hr.
OPERATING HOURS (100 LB. CYLINDER)	71 / 27 hours	29 / 11 hours
OPERATING HOURS (40 LB. CYLINDER)	29 / 11 hours	N/A
OPERATING HOURS (20 LB. CYLINDER)	14 / 5 hours	N/A
SUGGESTED CYLINDER SIZE	100 lb.	100 lb.
HEATING AREA	2,000 sq. ft.	5,000 sq. ft.
DIMENSIONS (LxWxH)	17.4x17.4x21.8in.	17.4x17.4x27.4in.
SHIP WT.	17 lb.	18 lb.
NET WT.	13 lb.	14 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
68-5010	Two cylinder manifold – Connects any two propane cylinders	All models



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.