



An
Employee
Owned
Company

JCW Series

Industrial Cold Water Pressure Washers

Gasoline — Portable — Belt Drive



JCW-3504-2MHB

The JCW Series is an ideal choice for tough cleaning jobs. Effectively strip coatings, clean large properties and remove build-up on ships.

PUMP

- Equipped with Mi-T-M Pressure Relief Start (JCW-3003, JCW-3504 and JCW-4004 models)
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

FRAME

- Powder coated steel frame
- Two-piece belt guard
- 13-inch flat-free tires (10-inch tires on JCW-2403 and JCW-2703 models)

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking hose
- Insulated trigger gun

LIMITED WARRANTIES

- 1 year Mi-T-M unloader
- 3 year Honda engine
- 7 year AR pump

CERTIFICATION

- ETL Certified – US



JCW Series

Cold Water – Gasoline – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JCW-2403-0MHB	2400	2.8	196cc Honda GX200 OHV	AR	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MHB	2700	2.4	196cc Honda GX200 OHV	AR	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-3003-2MHB	3000	3.0	270cc Honda GX270 OHV ⁺	AR	Mi-T-M, adjustable pressure	36in.	39.5x28.5x26in.	232 lb.	178 lb.
JCW-3504-2MHB	3500	3.7	389cc Honda GX390 OHV ⁺	AR	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.
JCW-4004-2MHB	4000	3.5	389cc Honda GX390 OHV ⁺	AR	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

⁺49 state engine. Not for sale in California.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/8-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0082	External bypass system – Allows more water into the system to protect from heat build-up; attaches to pump	3000 to 4000-PSI models
CX-0085	External bypass system – Allows more water into the system to protect from heat build-up; attaches to base plate	3000 to 4000-PSI models



⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.