



An  
Employee  
Owned  
Company

## JP Series

### Gasoline — Direct Drive Portable

The powerful JP Series pressure washers are excellent for blasting away mud and muck from equipment and buildings.

#### PUMP

- Equipped with Mi-T-M Pressure Relief Start
- Forged brass manifold
- Thermal relief valve
- In-line water strainer

#### FRAME

- Powder coated steel frame
- 10-inch flat-free tires

## Industrial Cold Water Pressure Washers



JP-3504-3MKB

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15° and 25°
- 50-foot x 3/8-inch non-marking hose
- Insulated trigger gun

#### LIMITED WARRANTIES

- 1 year unloader
- 3 year engine
- 7 year pump

#### CERTIFICATION

- ETL Certified – US (Select models, see chart)

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB*	2400	2.4	196cc Honda GX200 OHV*	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB*	2700	2.4	196cc Honda GX200 OHV*	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MKB	2700	2.4	208cc Kohler CH270 OHV*	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MMB	2700	2.4	212cc Mi-T-M OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB*	3000	3.0	270cc Honda GX270 OHV*	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MKB	3000	3.0	277cc Kohler CH395 OHV*	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MMB	3000	3.0	300cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB*	3500	3.5	389cc Honda GX390 OHV*	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MKB	3500	3.5	429cc Kohler CH440 OHV*	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MMB	3500	3.5	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB*	4000	3.5	389cc Honda GX390 OHV*	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

\*49 state fuel tank. Not for sale in California. \*ETL Certified – US.

# JP Series

## Cold Water – Gasoline – Direct Drive – Portable

### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
851-0338	50-foot x 3/4-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

### OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0083	External bypass system – Allows more water into the system to protect from heat build-up	JP-2403 & JP-2703 models
CX-0084	External bypass system – Allows more water into the system to protect from heat build-up	JP-3504 & JP-4004 models



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).