



An  
Employee  
Owned  
Company

# Cold Water Pressure Washer Trailers

## Industrial Gasoline – Belt Drive Trailer-Mount Pressure Washers

Easy to tow and equipped with a belt drive pump, the compact cold water trailers are durable and perfect for cleaning on the go.



JPC-3005-0MGM-T with electric start option, CX-0127

### TRAILER

- Tubular powder coated steel frame
- 2-inch ball hitch
- Fixed jack with drop leg pad
- LED lights
- (2) ST205-75R load range D nitrogen filled and balanced 15-inch radial tires
- Durable high density polyethylene fenders with integrated step and pad
- Plug and play wiring connection for easy installation and removal of tongue
- 3500-lb. axle with EZ lube spindles

### PUMP

- Adjustable pressure unloader
- Forged brass manifold
- Thermal relief valve
- Remote oil drain

### ENGINE

- Recoil start (Optional 12V electric start – battery not included)
- Remote oil drain

### COMPONENTS

- Powder coated steel frame
- Two-piece belt guard
- Mounting plate with rubber isolators

### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided hose
- Insulated trigger gun
- 200-gallon water tank with sump
- 150-foot high pressure hose reel
- Trailer tank bypass
- Full tank drain

### LIMITED WARRANTIES

- 3 year engine
- 7 year pump

Final assembly required: attach tongue and connect wiring harness. This unit will ship on a pallet.

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	FUEL TANK CAP.	DIMENSIONS (LxWxH)	GROSS VEHICLE WT.
JPC-3005-0MGH-T	3000	5.0	389cc Honda GX390 OHV+	General	Mi-T-M, factory preset	1.61 gallons	132.5x71.5x58in.	2,500 lb.
JPC-3005-0MGM-T	3000	5.0	420cc Mi-T-M OHV	General	Mi-T-M, factory preset	1.61 gallons	132.5x71.5x58in.	2,500 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory. +49 state engine. Not for sale in California.

OPTIONS: Options must be ordered with unit and cannot be added later.

PART NUMBER	DESCRIPTION	FITS MODEL
TX-0009	Adjustable trailer coupler hitch – Heavy-duty 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket with visual indication of proper closure around the ball – all to ensure a quick, easy and secure hook-up	All models
TX-0018	Lunette ring hitch – 3-inch integrated lunette ring for use with pintle hitches	All models
TX-0026	Backflow preventer – Prevents backflow of water into fresh water source. Required for use in many states and municipalities. Cannot be ordered with low pressure hose reel option, TX-0029.	All models
TX-0027	100-foot high pressure hose – Replaces 50-foot high pressure hose with 100-foot high pressure hose	All models
TX-0028	150-foot high pressure hose – Replaces 50-foot high pressure hose with 150-foot high pressure hose	All models
TX-0029	Low pressure hose reel – Fits 75-foot of 3/4-inch garden hose. Cannot be ordered with backflow preventer option, TX-0026.	All models
TX-0030	Backflow preventer and low pressure hose reel – Backflow preventer prevents backflow of water into fresh water source. Required for use in many states and municipalities. Low pressure hose reel replaces 50-foot high pressure hose with 150-foot high pressure hose	All models
CX-0127	Electric start – battery not included – For easy starting	JPC-3005-0MGH-T
CX-0128	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	All models
CX-0141	Electric start – battery not included – For easy starting	JPC-3005-0MGM-T

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

