



An
Employee
Owned
Company

Hot Water Pressure Washer Trailer

Industrial Gasoline – Belt Drive Trailer-Mount Pressure Washer

Easy to tow and equipped with a 12V Beckett burner, the compact hot-water trailer is durable and perfect for cleaning on the go.



JPH-4004-0MGH-T shown with front panel option, HX-0325

TRAILER

- Tubular powder coated steel frame
- 2-inch ball hitch
- Fixed jack with drop leg pad
- LED lights
- (2) ST205-75R load range D nitrogen filled and balanced 15-inch radial tires
- Speed rating M (81 mph)
- Durable high density polyethylene fenders with integrated step and pad
- Plug and play wiring connection for easy installation and removal of tongue
- 3500-lb. axle with EZ lube spindles

PUMP

- Adjustable pressure unloader
- Forged brass manifold
- Thermal relief valve
- Remote oil drain

ENGINE

- 12V electric start – battery not included
- Remote engine start and choke

COMPONENTS

- ½-inch schedule 80 pipe-coil with 4-pancake heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient

SAFETY FEATURES

- 250°F high temperature safety limit switch
- Thermal relief valve
- High pressure relief valve

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x ¾-inch steel wire-braided hose
- 50-foot garden hose
- Adjustable pressure insulated dual lance with trigger gun
- 200-gallon water tank with sump
- 150-foot high pressure hose reel
- 75-foot garden hose reel
- Trailer tank bypass
- Full tank drain

LIMITED WARRANTIES

- 3 year coil
- 3 year Honda engine
- 7 year General pump

Final assembly required: attach tongue and connect wiring harness. This unit will ship on a pallet.

| MODEL NUMBER | PSI | GPM | DISPLACEMENT/ENGINE | PUMP | ENGINE FUEL TANK CAP. | BURNER FUEL TANK CAP. | BURNER FUEL CONS. | BTU PER HOUR | DIMENSIONS (LxWxH) | GROSS VEHICLE WT. |
|-------------------|------|-----|------------------------|---------|-----------------------|-----------------------|-------------------|--------------|--------------------|-------------------|
| JPH-4004-0MGH-T ⚡ | 4000 | 3.7 | 389cc Honda GX390 OHV+ | General | 1.61 gallons | 10.0 gallons | 2.76 gph | 386,400 | 132.5x71.5x64in. | 2,900 lb. |

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

+49 state engine. Not for sale in California.

⚡ Equipped with electric start – battery not included.

Hot Water Pressure Washer Trailer

Industrial Gasoline – Belt Drive

ACCESSORIES:

| PART NUMBER | DESCRIPTION | FITS MODEL |
|--------------|--|-----------------|
| 20-1366A52 | Black powder coated rain cap – Protects boiler from moisture build-up when unit is left outside, octagonal | JPH-4004-OMGH-T |
| AW-6000-1006 | Equipment cover – Keeps your equipment clean, dry and looking like new | JPH-4004-OMGH-T |
| AW-8400-0021 | Low pressure detergent injector – Allows the user to apply the recommended detergents | JPH-4004-OMGH-T |

OPTIONS: *Options must be ordered with unit and cannot be added later.*

| PART NUMBER | DESCRIPTION | FITS MODEL |
|-------------|---|-----------------|
| TX-0009 | Adjustable trailer coupler hitch – Heavy-duty 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket with visual indication of proper closure around the ball – all to ensure a quick, easy and secure hook-up | JPH-4004-OMGH-T |
| TX-0018 | Lunette ring hitch – 3-inch integrated lunette ring for use with pintle hitches | JPH-4004-OMGH-T |
| TX-0025 | Backflow preventer – Prevents backflow of water into fresh water source. Required for use in many states and municipalities. | JPH-4004-OMGH-T |
| TX-0027 | 100-foot high pressure hose – Replaces 50-foot high pressure hose with 100-foot high pressure hose | JPH-4004-OMGH-T |
| TX-0028 | 150-foot high pressure hose – Replaces 50-foot high pressure hose with 150-foot high pressure hose | JPH-4004-OMGH-T |
| HX-0146 | Hour meter – Displays the number of hours unit has been in operation | JPH-4004-OMGH-T |
| HX-0324 | Adjustable thermostat – Operator is able to adjust outlet water temperature between 98°-248°F | JPH-4004-OMGH-T |
| HX-0325 | Removable painted front panel – Provides a protective panel and gives the unit a more finished look | JPH-4004-OMGH-T |



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.