



Kerosene Forced Air

Portable Heaters

75,000 up to 190,000 BTU



MH-0135-RM10

Portable kerosene forced air heaters are ideal for use in well ventilated garages, workshops and jobsites.

MOTOR

- Heavy-duty, cast aluminum enclosed electric motor

BURNER HEAD

- 1-piece cast aluminum

COMPONENTS

- High performance fan
- Integral overheat and flame-out safety
- Fuel gauge
- Sure start ignition for cold temperature starts
- Dual connector ignition
- Flat-free tires

CERTIFICATION

- CSA Certified – US and Canada

FACTORY TESTED FOR MULTIPLE FUELS

- Kerosene
- JP8/Jet A fuel
- No. 1 and No. 2 fuel oil
- No. 1 and No. 2 diesel fuel

IMPORTANT NOTES

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

Kerosene Forced Air

Portable Heaters – 75,000 up to 190,000 BTU

MODEL NUMBER	MH-0075-RM10	MH-0135-RM10	MH-0190-RM10
HEAT OUTPUT	75,000 BTU	135,000 BTU	190,000 BTU
HOT-AIR FLOW	173 CFM	321 CFM	409 CFM
AIR PUMP PRESSURE	5.5 PSI	6.0 PSI	7.5 PSI
AC POWER	120V, 60Hz, 1.3 Amps	120V, 60Hz, 2.1 Amps	120V, 60Hz, 2.5 Amps
MOTOR SIZE	5/16 HP	27/64 HP	19/32 HP
FUEL TANK CAPACITY	5.3 gallons	10.6 gallons	13.2 gallons
FUEL CONSUMPTION	0.55 gal./hr.	0.97 gal./hr.	1.37 gal./hr.
MAX. OPERATING HOURS	9.6 hours	10.9 hours	9.6 hours
HEATING AREA	1,875 sq. ft.	3,375 sq. ft.	4,750 sq. ft.
MULTI-FUEL CAPABLE	Yes	Yes	Yes
DIMENSIONS (LxWxH)	29x12x16in.	35x22x26in.	40x23x25in.
SHIP WT.	33 lb.	63 lb.	71 lb.
NET WT.	28 lb.	54 lb.	62 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.



MH-0075-RM10



Simple On/Off Operation



Flat-Free Tires



Sure Start Ignition