



An
Employee
Owned
Company

Kerosene Forced Air

Industrial
75,000 up to 600,000 BTU

Easily heat large areas with the portable kerosene forced air heaters. They come in various sizes to provide reliable heat wherever needed.



MH-0190-0M11

MOTOR

- Heavy-duty, cast aluminum enclosed electric motor

BURNER HEAD

- One-piece cast aluminum

COMPONENTS

- Easy assembly
- Built-in temperature control thermostat with control dial
- High performance fan
- Integral overheat and flame-out safety
- Fuel gauge
- Sure start ignition for cold temperature starts
- Dual connector ignition
- Flat-free tires (Pneumatic tires on MH-400 and MH-0600 models)

LIMITED WARRANTY

- 1 year

CERTIFICATION

- CSA Certified – US and Canada (MH-0075, MH-0135, MH-0190 and MH-0215 models)
- ETL Certified – US and Canada (MH-0400 and MH-0600 models)

FACTORY TESTED FOR MULTIPLE FUELS

- Kerosene
 - JP8/Jet A fuel
 - No. 1 and No. 2 fuel oil
 - No. 1 and No. 2 diesel fuel
- Note: Not approved for bio-fuel.

IMPORTANT NOTES

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

MODEL NUMBER	MH-0075-0M11	MH-0135-0M11	MH-0190-0M11	MH-0215-0M11	MH-0400-0M11	MH-0600-0M11
HEAT OUTPUT	75,000 BTU	135,000 BTU	190,000 BTU	215,000 BTU	400,000 BTU	600,000 BTU
HOT-AIR FLOW	173 CFM	321 CFM	409 CFM	409 CFM	1,400 CFM	3,000 CFM
AIR PUMP PRESSURE	5.5 PSI	6.0 PSI	7.5 PSI	7.0 PSI	125 PSI	170 PSI
AC POWER	120V, 60Hz, 1.3 Amps	120V, 60Hz, 2.1 Amps	120V, 60Hz, 2.5 Amps	120V, 60Hz, 2.7 Amps	120V, 60Hz, 3.3 Amps	120V, 60Hz, 5.5 Amps
MOTOR SIZE	1/5 HP	1/3 HP	1/2 HP	1/2 HP	1/2 HP	5/8 HP
FUEL TANK CAPACITY	5.3 gallons	10.6 gallons	13.2 gallons	13.2 gallons	24.0 gallons	40.0 gallons
FUEL CONSUMPTION	0.55 gal./hr.	0.97 gal./hr.	1.37 gal./hr.	1.58 gal./hr.	3.00 gal./hr.	4.50 gal./hr.
MAX. OPERATING HOURS	9.5 hours	11.0 hours	10.0 hours	8.0 hours	8.0 hours	8.9 hours
HEATING AREA	1,875 sq. ft.	3,375 sq. ft.	4,750 sq. ft.	5,375 sq. ft.	10,000 sq. ft.	15,000 sq. ft.
MULTI-FUEL CAPABLE	Yes	Yes	Yes	Yes	Yes	Yes
DIGITAL TEMP. READ-OUT	Yes	Yes	Yes	Yes	Yes	Yes
ERROR INDICATOR READ-OUT	Yes	Yes	Yes	Yes	Yes	Yes
DIMENSIONS, CARTON (LxWxH)	31x13x16in.	39x15x22in.	41x17x22in.	41x17x22in.	53x21x29in.	84x44x52in.
SHIP WT.	33 lb.	62 lb.	70 lb.	70 lb.	163 lb.	330 lb.
NET WT.	28 lb.	54 lb.	62 lb.	62 lb.	143 lb.	264 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.