



An
Employee
Owned
Company

Recovery & Recycle System

Water Treatment Systems

Making a positive impact on our environment for today and future generations.

PWR Series



PWR Series

Recovery & Recycle System

THE PORTABLE WATER RECOVERY SERIES CAPTURES, FILTERS AND RECYCLES WASH WATER FOR REUSE OR PROPER DISPOSAL ON AND OFF JOBSITES.



PWR-10-OME1 shown with standard accessories, dual filter option, WX-0109 and wheel kit option, WX-0106 (WX options not included with standard PWR unit)

FEATURES

- 1/3 HP transfer pump
- Oil absorbing boom/stick
- Vacuum tank drain
- 3-stage vacuum motor
- Stainless-steel suction head
- Cam lock fittings
- 50-foot vacuum hose
- 55-gallon tank capacity
- 20-foot water berm



NEMA 5-20P,
20-amp plug



Filter wrench will assist in removing and attaching the filter housing for required maintenance of filter cartridge (included with PWR Series manual pack)

| MODEL NUMBER | VACUUM MOTOR | TANK CAPACITY | FILTER PUMP | WATER BERM | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|--------------|---------------------------------|---------------|------------------------------|------------|--------------------|----------|---------|
| PWR-10-OME1 | 3-stage, 1500W, 12.5A full load | 55-gallons | 1/3 HP, 120V, 1Ø, 8.0A, 60Hz | 6in.x20ft. | 48x42x60in. | 340 lb. | 290 lb. |

ACCESSORIES:

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 19-0216 | 20-micron poly filter – 20-inch, pleated |
| 19-0302 | 10-micron cartridge filter – 20-inch |
| 21-0306 | Stainless-steel suction head |
| 33-0520 | Water berm – 6-inch x 20-foot |
| 33-0529 | Oil absorbing boom – Oil sock for inside of tank |
| 855-0057 | 50-foot x 1½-inch vacuum hose – Can have up to 100-foot of extension hose |

OPTIONS:

| PART NUMBER | DESCRIPTION |
|-------------|---|
| TX-0010 | Adjustable trailer coupler hitch, 2-inch – Replaces the standard 2-inch ball hitch with a 2-inch trailer hitch with pin-style fastener trailer coupler and hinged ball socket; for AW-9000-0010 trailer package |
| TX-0019 | Lunette ring hitch, 3-inch – Replaces the standard 2-inch ball hitch with a 3-inch integrated lunette ring for use with pintle hitches; for AW-9000-0010 trailer package |
| WX-0106 | Wheel kit – Includes two flat-free tires, powder coated steel frame and handle |
| WX-0109 | Dual filters – Uses 30-micron filter #19-0216 and 10-micron filter #19-0302. Includes one set of filters installed in housings and one set of replacement filters. |
| WX-0129 | Dual filters for PWR-10-OME1 trailer-mount package – Uses 30-micron filter #19-0216 and 10-micron filter #19-0302. Includes one set of filters installed in housings and one set of replacement filters. |

PWR Series

Portable Water Recovery Trailer Packages

PWR SERIES TRAILER PACKAGES INCLUDE:

- Portable water recovery trailer, AW-9000-0010
- PWR-10-0ME1 with WX-0129 option
- Hot water pressure washer - Choose from HVS-3505-1H6G or HDS-3505-1H6G

Portable Water Recovery Trailer, AW-9000-0010

- 5-foot x 8½-foot dual-axle trailer
- 200-gallon water tank enclosed in powder coated steel frame
- Jack with pad
- Rubber mounted sealed lights
- 50-foot inlet garden hose with hose reel
- 100-foot high pressure hose with hose reel
- Tank feed for pressure washer
- Option to directly feed water from inlet hose reel

PWR-10-0ME1 with WX-0129 Option for Trailer

Includes all standard PWR Series features, as well as:

- 2 cartridge filters – 20 and 10-micron; includes one set of replacement filters. Other sizes are available, consult dealer.
- Automatic discharge to outlet valve for reuse or discharge

Hot Water Pressure Washer, HVS-3505-1H6G with HX-0252 Option for Trailer

- 3500 PSI @ 4.2 GPM
- GX630 Honda OHV gasoline engine
- Belt drive triplex piston clutch driven General pump
- Heavy-duty powder coated steel square tube skid frame
- Powder coated steel coil wrap and control panel
- Trailer tank feed
- 80-mesh inlet Y-strainer
- Generator wired for burner and PWR-10-0ME1 with dual filters option, WX-0129
- Consult dealer for additional options available for the HVS-3505-1H6G

Hot Water Pressure Washer, HDS-3505-1H6G with HX-0253 Option for Trailer

- 3500 PSI @ 4.2 GPM
- GX630 Honda OHV gasoline engine
- Belt drive triplex piston clutch driven General pump
- Heavy-duty powder coated steel square tube skid frame
- Stainless-steel coil wrap and control panel
- Trailer tank feed
- 80-mesh inlet Y-strainer
- Generator wired for burner and PWR-10-0ME1 with dual filters option, WX-0129
- Consult dealer for additional options available for the HDS-3505-1H6G



PWR Series Trailer Package

PWR Series Application



An
Employee
Owned
Company

50 Mi-T-M Drive | Peosta, IA 52068
(800) 553-9053 | www.mitm.com