

An Employee Owned Company

## Propane Forced Air Portable Heaters

### 40,000 up to 375,000 BTU



These lightweight, portable heaters are ideal for drying and heating well ventilated workspaces. Add a propane cylinder, plug it in and stay comfortable while you work.

#### FRAME

- Heavy-duty steel construction
- Easy-lift handle for portability

#### COMPONENTS

- High performance fan
- Automatic shut-off if power is interrupted or flame is extinguished
- Enclosed gas controls
- Electronic ignition
- · One-touch ignition and heat control for easy operation

#### LIMITED WARRANTY

• 1 year

#### CERTIFICATIONS

- CSA Certified US
- CSA Blue Star Certified US

#### **IMPORTANT NOTES**

- · Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

# Propane Forced Air Portable Heaters – 40,000 up to 375,000 BTU

MODEL NUMBER	MH-0060-LM10	MH-0150-LM10	MH-0150-LMT0*	MH-0150-NM10*	MH-0375-LM10*
HEAT OUTPUT	40-50-60,000 BTU	120-135-150,000 BTU	150,000 BTU	150,000 BTU	225-375,000 BTU
HOT-AIR FLOW	300 CFM	400 CFM	400 CFM	435 CFM	1,500 CFM
AC POWER	120V, 60Hz, Less than 1.0 Amp	120V, 60Hz, 1.45 Amps			
MOTOR SIZE	1/10 HP	1/9 HP	1/9 HP	1/9 HP	1/5 HP
FUEL	Propane	Propane	Propane	Natural Gas	Propane
FUEL CONSUMPTION	1.9 / 2.3 / 2.8 lb./hr.	5.5 / 6.2 / 6.9 lb./hr.	6.9 lb./hr.	146 cu. ft./hr.	10.4 to 17.4 lb./hr.
REQUIRED CYLINDER SIZE	20 lb.	100 lb.	100 lb.	N/A	(2) 100 lb.
MAX. OPERATING HOURS (PER REQUIRED CYLINDER SIZE)	10.5 hours	18.0 hours	18.0 hours	N/A	11.5 hours
HEATING AREA	1,500 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	9,000 sq. ft.
ADJUSTABLE THERMOSTAT	No	No	Yes	Yes	Yes
ADJUSTABLE HEIGHT ANGLE	Yes	Yes	Yes	Yes	No
HOSE AND REGULATOR	10ft.	10ft.	10ft.	No	10ft.
DIMENSIONS (LxWxH)	18.1x7.1x13in.	25.1x8.7x15.4in.	25.1x8.7x15.4in.	25.1x9x15.5in.	34x12.6x18.5in.
SHIP WT.	19 lb.	29 lb.	29 lb.	35 lb.	49 lb.
NET WT.	15 lb.	23 lb.	23 lb.	24 lb.	41 lb.

FITS MODELS

#### \*Includes thermostat.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

ACCESSORY:					
PART NUMBER	DESCRIPTION				

68-5010	Two cylinder manifold – Connects any two propane cylinders	All models

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.