



An
Employee
Owned
Company

Propane Radiant Outdoor Patio

Industrial

Variable Output up to 50,000 BTU

Keep warm on cool nights with this user-friendly patio heater, designed with a convenient wheel kit to move wherever warmth is needed.

FRAME

- Heavy-duty, stainless-steel emitter screen
- Rust resistant reflector material
- Four-piece reflector assembly
- Large diameter support post
- Wheel kit for easy maneuverability

HEAT OUTPUT

- Variable heat settings
- 360° heat radius for even heating

COMPONENTS

- Wind resistant burner system prevents flame from being extinguished and has automatic shut-off if flame is extinguished
- Built-in safety tip-over switch
- Piezo spark push-button controls
- Hose and regulator

LIMITED WARRANTY

- 1 year

CERTIFICATION

- ETL Certified – US and Canada

IMPORTANT NOTES

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Extremely hot during operation. Keep children, animals and all combustible objects away from heater.



MH-0042-PM11

| | |
|-----------------------------------|-------------------------|
| MODEL NUMBER | MH-0042-PM11 |
| HEAT OUTPUT* | L-22,500 / H-50,000 BTU |
| FUEL CONSUMPTION | 2.3 lb./hr. |
| OPERATING HOURS (20 LB. CYLINDER) | 8.5 hours |
| SUGGESTED CYLINDER SIZE | 20 lb. (not included) |
| HEATING AREA | 290 sq. ft. |
| MANIFOLD PRESSURE | 11in. WC |
| BASE DIAMETER | 18in. |
| DIMENSIONS (LxWxH) | 32.3x32.3x88in. |
| SHIP WT. | 38 lb. |
| NET WT. | 33 lb. |

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

**Heat output is at Low and High settings.*



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.