

30-Gallon

Two Stage – Diesel

Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Generator:

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- Comes standard with
(2) 120V, 20A and
(1) 240V, 20A receptacles

Engine:

- Electric start - battery, box and cables not included
- Glow plug equipped engine for easy starting in cold temperatures

Frame:

- Powder coated ASME coded 30-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard

Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

Limited Warranties:


- 2 year alternator
- 2 year pump exchange (see page 71 for more information)
- 3 year Kohler engine

Certification:

- ASME Boiler and Pressure Vessel Code - UM



AG2-SKD9-30M



Designed for the agricultural, construction and industrial industries, the 30-gallon air compressor/generator is powered by a diesel engine. This machine fits on the back of a service truck for big jobs in remote locations.

| MODEL NUMBER | CFM @ 90 PSI | CFM @ 175 PSI* | MAX. OUTPUT | ALTERNATOR WATTAGE | | RECEPTACLES | HORSEPOWER/ENGINE | COMPRESSOR | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|--------------|--------------|----------------|-------------|--------------------------|---------------------------|------------------------------------|-------------------------|----------------------|--------------------|----------|---------|
| | | | | CONT. WITH COMP. ON-LOAD | CONT. WITH COMP. OFF-LOAD | | | | | | |
| AG2-SKD9-30M | 16.4 | 15.7 | 3000 watts | 2300 watts | 2750 watts | (2) NEMA 5-20R, (1) NEMA L6-20R | 9.1 HP Kohler KD440 OHV | Two stage, cast iron | 41x23x47in. | 554 lb. | 489 lb. |

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

| PART NUMBER | DESCRIPTION | FITS MODEL |
|--------------|---|--------------|
| 70-0380 | Engine oil drain extension | AG2-SKD9-30M |
| AW-6000-1002 | Equipment cover | AG2-SKD9-30M |
| IX-0001 | Vibration isolator pads - Isolators protect the unit from vibration during use; Recommended for models that are mounted in service truck applications | AG2-SKD9-30M |