

Work Pro® Series

Compressor Pump:

- Splash oil lubricated aluminum crankcase
- Stainless-steel braided discharge hose
- Oil level sight indicator

Motor:

- Thermal overload motor protection

Frame:

- Powder coated 8-gallon twin tank receivers
- 1/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tire (Two-stage models have two tires)

Components:

- Regulator and two gauges for tank and outlet pressure
- Drain and pressure relief valves
- Fly wheel
- Industrial-grade pressure switch (Electric model)
- Quality pilot valve unloader (Gasoline models)

Limited Warranties:

- 1 year compressor pump
- 1 year electric motor
- 1 year Mi-T-M engine
- 3 year Honda engine

Certifications:

- CSA Certified - US and Canada (AM1-PE15-08WP)

2 NEW MODELS FOR 2017



NEMA 5-15P,
15-amp plug

Featuring advanced technology and performance, the Mi-T-M single or two stage air compressor can power everything from impact wrenches to nail guns. The perfect solution for both small jobs around the house and big jobs around the shop.



AM1-PM65-08WP

Single or Two Stage – Electric/Gasoline

ELECTRIC MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08WP	7.3 @ 90	1.5 HP, 115V, 13.2A	Single stage, aluminum	8-gallon	NEMA 5-15P	44.5x18.5x25in.	160 lb.	140 lb.
GASOLINE MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH06-08WP	7.1 @ 90	196cc Honda GX200 OHV	Single stage, aluminum	8-gallon	Pneumatic	44.5x18.5x27in.	160 lb.	135 lb.
AM1-PM06-08WP	7.1 @ 90	212cc Mi-T-M OHV	Single stage, aluminum	8-gallon	Cable throttle	44.5x18.5x27in.	160 lb.	135 lb.
AM1-PH65-08WP	13.9 @ 90	196cc Honda GX200 OHV	Single stage, aluminum	8-gallon	Pneumatic	44.5x18.5x27in.	170 lb.	145 lb.
AM1-PM65-08WP	13.9 @ 90	212cc Mi-T-M OHV	Single stage, aluminum	8-gallon	Cable throttle	44.5x18.5x27in.	170 lb.	145 lb.
AM2-PH09-08WP	17.2 @ 175*	270cc Honda GX270 OHV	Two stage, aluminum	8-gallon	Pneumatic	44x26x31in.	200 lb.	175 lb.
AM2-PM09-08WP	17.2 @ 175*	300cc Mi-T-M OHV	Two stage, aluminum	8-gallon	Cable throttle	44x26x31in.	200 lb.	175 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
70-0357	Engine oil drain extension	Single stage models	AX-0003	Manual drain/regulator/metal bowl	All models
70-0358	Engine oil drain extension	Two stage models	AX-0015	Electric start - battery and cables not included	AM2-PH09-08WP
AW-6000-1002	Equipment cover	All models	IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0015	AM2-PH09-08WP
AX-0002	Auto drain/regulator/plastic bowl	AM1-PE15-08WP			