

20-Gallon

The 20-gallon electric air compressor provides extra air storage that allows you to operate multiple tools at the same time and is the perfect solution for contractor job sites.

Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Motor:

- Auto start/stop - continuous run optional
- Thermal overload motor protection

Frame:

- Powder coated ASME coded 20-gallon receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tires

Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch

Limited Warranties:


- 1 year electric motor
- 2 year pump exchange
(see page 66 for more information)

Certifications:

- CSA Certified - Canada only
- ASME Boiler and Pressure Vessel Code - UM



AM1-PE02-20M



NEMA 5-15P, 15-amp plug
NEMA 5-20P, 20-amp plug

Single Stage – Electric

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-20M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage, cast iron	20-gallon	NEMA 5-15P	40x24x32in.	265 lb.	196 lb.
AM1-PE02-20M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage, cast iron	20-gallon	NEMA 5-20P	40x24x32in.	272 lb.	203 lb.

Accessory & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0008	Dual control - continuous run & auto start/stop	All models