

# 8-Gallon

Designed with both contractors and remodelers in mind, the 8-gallon two stage air compressor is perfect for job site tasks requiring a higher CFM and air pressure.

### Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

### Frame:

- Powder coated 8-gallon twin tank receivers
- $\frac{3}{16}$ -inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard
- Flat-free tires

### Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 $\frac{1}{2}$ -inch fly wheel
- Quality pilot valve unloader

### Limited Warranties:

- 2 year pump exchange  
(see page 66 for more information)
- 3 year Honda and Kohler engines



AM2-PH09-08M

## Two Stage – Gasoline

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler CH395 OHV	Two stage, cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.

\*Equipped with 150-PSI maximum rated regulator.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models
AX-0003	Manual drain/regulator/metal bowl	All models
AX-0015	Electric start - battery and cables not included	AM2-PH09-08M
IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0015	AM2-PH09-08M