

### Two Stage – Gasoline



AM2-SH09-20M shown with electric start option, AX-0015

#### Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

#### Frame:

- Powder coated ASME coded 20-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard
- 13-inch flat-free tires (AM2-PH09-20M)

#### Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

#### Limited Warranties:

- 2 year pump exchange (see page 71 for more information)
- 3 year Honda engine

#### Certification:

- ASME Boiler and Pressure Vessel Code - UM

This model features a powerful and efficient two stage compressor designed to maximize productivity. The versatility of the 20-gallon air compressor offers extra air storage and comes in stationary or portable models.

PORTABLE MODEL								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	20-gallon	Pneumatic	46x26x39.5in.	356 lb.	306 lb.

  

STATIONARY MODEL								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-20M	17.2 @ 175	270cc Honda GX270 OHV	Two stage, cast iron	20-gallon	Pneumatic	37x18x38in.	356 lb.	306 lb.

\*Equipped with 150-PSI maximum rated regulator.

#### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
854-0093	Service mount truck kit - recommended for models that are mounted in service truck applications	AM2-SH09-20M	AX-0015	Electric start - battery and cables not included	All models
AW-0007-0196	Rear lifting handle (N/A for models with AX-0017 option)	AM2-PH09-20M	AX-0017	Electric start - battery and cables included	All models
AW-6000-1002	Equipment cover	All models	IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order electric start option, AX-0015	All models
AX-0003	Manual drain/regulator/metal bowl	All models			