

CD Series

The CD Electric Series features a powder coated steel mounting plate with center balanced lift and four rubber isolators. Built for all-purpose cleaning, this lightweight and portable pressure washer is perfect for homeowners and small industrial jobs where exhaust fumes are prohibited.

Pump:

- Forged brass manifold
- Thermal and safety relief valves
- Low pressure detergent injector

Motor:

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 35-foot, 15-amp power cord (20-amp on CD-1502 models) with ground fault circuit interrupter, GFCI

Unit Includes:

- Variable high/low pressure nozzle (3MUH models)
- 15° high/low pressure nozzle (2MUH models)
- 25-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off

Limited Warranties:


- 1 year electric motor
- 7 year pump

Certifications:

- CSA Certified - US and Canada



CD-1502-3MUH



NEMA 5-15P,
15-amp plug

NEMA 5-20P,
20-amp plug

Cold Water – Electric – Direct Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	MI-T-M NO.	UNLOADER	PLUG TYPE	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CD-1002-3MUH	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	AR	3-0362	Adjustable pressure	NEMA 5-15P	36in.	20x11.5x14in.	70 lb.	58 lb.
CD-1002-2MUH*	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	General	3-0278	Adjustable pressure	NEMA 5-15P	36in.	20x11.5x14in.	71 lb.	66 lb.
CD-1502-3MUH	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	36in.	20x11.5x14in.	76 lb.	70 lb.
CD-1502-2MUH*	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	36in.	20x11.5x14in.	76 lb.	70 lb.

*Pump accepts incoming water up to 175°F

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
18-0370	Rotating nozzle	CD-1502 models	50-0161	High pressure detergent injector	All models
18-0371	Rotating nozzle	CD-1002 models	CX-0030	50-ft. x 3/8-in. non-marking hose	All models