

The CW Premium Gasoline Series features a powder coated steel frame and base plate with 1¼-inch tube handles, two-piece belt guard and flat-free tires. Equipped with a heavy-duty belt drive system, this series is deemed the workhorse of the Mi-T-M industrial pressure washer line.

## CW Premium Series



CW-4004-5MGH

### Pump:

- External bypass system allows more water into the system to protect from heat build-up
- Forged brass manifold (Nickel plated brass on 4000-PSI model)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### Unit Includes:

- Quick connect nozzles - 0°, 15°, 25° and 40°
- 50-foot x ¾-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off

### Limited Warranties:

- 1 year Mi-T-M unloader (3500 and 4000-PSI models)
- 3 year Honda and Vanguard engines
- 10 year pump

### Certifications:

- Intertek - Certified to UL-1776

## Cold Water – Gasoline – Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2505-4MGH	2500	4.4	389cc Honda GX390 OHV	General	3-0202	Preset pressure	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3004-4MGH	3000	3.5	389cc Honda GX390 OHV	General	3-0202	Preset pressure	36in.	45.5x28x26in.	290 lb.	216 lb.
CW-3504-5MGH	3500	3.8	389cc Honda GX390 OHV	General	3-0203	Mi-T-M, preset pressure	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MGH	4000	3.5	389cc Honda GX390 OHV	General	3-0075	Mi-T-M, preset pressure	48in.	46x28x30in.	290 lb.	216 lb.
CW-4004-5MV0	4000	4.0	480cc Vanguard OHV, electric start - battery included	General	3-0075	Mi-T-M, preset pressure	48in.	46x28x30in.	330 lb.	256 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0045	Electric start - battery included	All Honda models
851-0338	50-ft. x ¾-in. non-marking hose	All models	CX-0054	Roll cage	All Honda models
AW-8400-0021	Low pressure detergent injector	All models	CX-0055	Roll cage	CW-4004-5MV0
CX-0005	48-in. insulated dual lance	All models			