

Use an inverter generator to charge and power your equipment during recreational activities or while working on a job site.




Portable Generators

Model Shown:
GEN-3000-IMMO

Inverters 2000 & 3000-Watt – Gasoline

Alternator	Engine	Frame	Components	Limited Warranties
<ul style="list-style-type: none"> • Copper windings • Total harmonic distortion (THD) less than 3% 	<ul style="list-style-type: none"> • Low-oil shutdown • Recoil start 	<ul style="list-style-type: none"> • Insulated side panels reduce noise • Easy grip handle integrated into frame (Two handles on GEN-3000-IMMO) • Rear folding handle and two wheels for easy transport (GEN-3000-IMMO) 	<ul style="list-style-type: none"> • DC/battery charging • USB port for electronics • Idle control • USDA/USFS-approved spark arrestors 	<ul style="list-style-type: none"> • 1 year alternator • 1 year Mi-T-M engine
				<p>Certifications</p> <p>CSA Certified</p>

MODEL NO.	GEN-2000-IMMO	GEN-3000-IMMO
MAX. AC OUTPUT	2000 watts	3000 watts
RATED AC OUTPUT	1600 watts	2800 watts
DISPLACEMENT/ENGINE	79cc Mi-T-M OHV	212cc Mi-T-M OHV
ALTERNATOR	Copper windings	Copper windings
MAX. AMPS (120V)	16.7A	25A
CONT. AMPS (120V)	13.3A	23.3A
RECEPTACLES	(1) 120V, 20A duplex; (1) 12V DC 8.0A	(1) 120V, 20A duplex; (1) 120V, 30A twist lock; (1) 12V DC 8.3A
MAIN CIRCUIT BREAKER	Yes	Yes
RATED SPEED	3600 RPM	3600 RPM
DECIBEL RATING	63.0	68.0
FUEL CAPACITY	1.1 gallons	1.89 gallons
RUN TIME (AT HALF LOAD)	6.0 hours	6.75 hours
DIMENSIONS (LxWxH)	19.6x11.4x18in.	23.8x17x19.4in.
SHIP WT.	53 lb.	90 lb.
NET WT.	48 lb.	84 lb.



120V Duplex
All Models



NEMA L5-30R
120VAC
GEN-3000-IMMO

Inverter generator ratings represent no-load sound levels. Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

Consult factory for more information on these available accessories:

Parallel port boxes allow you to utilize the power of two units at once