

# JCW Series

## Cold Water Gasoline Belt Drive

The JCW Gasoline Series features a powder coated steel frame and base plate with 1¼-inch tube handles, two-piece belt guard and flat-free tires. This belt-driven pressure washer can handle even the toughest environments.

### Pump:

- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

### Unit Includes:

- Quick connect nozzles - 0°, 15°, 25° & 40°
- 50-foot x ¾-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off

### Limited Warranties:

- 1 year Mi-T-M unloader (3000, 3500 & 4000-PSI models)
- 3 year Honda engine
- 5 year Subaru engine
- 7 year pump

### Certifications:

- Intertek - Certified to UL-1776



JCW-4004-3MSB

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com)



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JCW-2403-0MHB	2400	2.8	196cc Honda OHV	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2403-0MRB	2400	2.8	211cc Subaru OHC	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MHB	2700	2.4	196cc Honda OHV	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-2703-0MRB	2700	2.4	211cc Subaru OHC	AR	3-0228	Adjustable pressure	36in.	37.5x22x25in.	171 lb.	121 lb.
JCW-3003-2MHB	3000	3.0	270cc Honda OHV	AR	3-0308	Mi-T-M, adjustable pressure	36in.	39.5x28.5x26in.	232 lb.	178 lb.
JCW-3003-2MSB	3000	3.0	265cc Subaru OHC	AR	3-0308	Mi-T-M, adjustable pressure	36in.	39.5x28.5x26in.	232 lb.	178 lb.
JCW-3504-2MHB	3500	3.7	389cc Honda OHV	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	245 lb.	191 lb.
JCW-3504-2MSB	3500	3.7	404cc Subaru OHC	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	245 lb.	191 lb.
JCW-4004-2MHB	4000	3.5	389cc Honda OHV	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.
JCW-4004-2MSB	4000	3.5	404cc Subaru OHC	AR	3-0308	Mi-T-M, adjustable pressure	48in.	39.5x28.5x26in.	249 lb.	195 lb.

### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	48-in. insulated dual lance	All models
851-0338	50-ft. x ¾-in. non-marking hose	All models	CX-0082	External bypass system - attaches to pump	3000 to 4000-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0085	External bypass system - attaches to base plate	3000 to 4000-PSI models